



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61K 9/00		(11) International Publication Number: WO 99/59544
A2		(43) International Publication Date: 25 November 1999 (25.11.99)
(21) International Application Number: PCT/JP99/02548		(74) Agents: ASAHINA, Tadao et al.; Osaka Plant of Takeda Chemical Industries, Ltd., 17-85, Jusohonmachi 2-chome, Yodogawa-ku, Osaka-shi, Osaka 532-0024 (JP).
(22) International Filing Date: 17 May 1999 (17.05.99)		(81) Designated States: AE, AL, AM, AU, AZ, BA, BB, BG, BR, BY, CA, CN, CU, CZ, EE, GD, GE, HR, HU, ID, IL, IN, IS, JP, KG, KR, KZ, LC, LK, LR, LT, LV, MD, MG, MK, MN, MX, NO, NZ, PL, RO, RU, SG, SI, SK, SL, TJ, TM, TR, TT, UA, US, UZ, VN, YU, ZA, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
(30) Priority Data: 10/135472 18 May 1998 (18.05.98) JP 10/219266 3 August 1998 (03.08.98) JP 10/222151 5 August 1998 (05.08.98) JP 11/5144 12 January 1999 (12.01.99) JP 11/15851 25 January 1999 (25.01.99) JP		Published Without international search report and to be republished upon receipt of that report.
(71) Applicant (for all designated States except US): TAKEDA CHEMICAL INDUSTRIES, LTD. [JP/JP]; 1-1, Doshomachi 4-chome, Chuo-ku, Osaka-shi, Osaka 541-0045 (JP).		
(72) Inventors; and (75) Inventors/Applicants (for US only): SHIMIZU, Toshihiro [JP/JP]; 5-1-608, Kitano 6-chome, Itami-shi, Hyogo 664-0007 (JP). MORIMOTO, Shuji [JP/JP]; 1-25, Matsugaoka, Senriyama, Suita-shi, Osaka 565-0843 (JP). TABATA, Tetsuro [JP/JP]; 9-A1-413, Yamadanishi 2-chome, Suita-shi, Osaka 565-0824 (JP).		
(54) Title: ORALLY DISINTEGRABLE TABLETS		
(57) Abstract <p>An orally disintegrable tablet, of the present invention, which comprises (i) fine granules having an average particle diameter of 400 μm or less, which fine granules comprise a composition coated by an enteric coating layer, said composition having 10 weight % or more of an acid-labile physiologically active substance and (ii) an additive, has superior disintegrability or dissolution in the oral cavity so that it can be used for treatment or prevention of various diseases, as an orally disintegrable tablet capable of being administered to the aged or children and easily administered without water. Also, because the tablet of the present invention contains fine granules having the average particle diameter such that it will not impart roughness in mouth, it can be administered easily without discomfort at the administration.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

DESCRIPTION

Orally Disintegrable Tablets

TECHNICAL FIELD

5 The present invention relates to an orally disintegrable tablet having a characteristic of fast disintegration in the oral cavity even without water.

BACKGROUND ART

10 Pharmaceutical solid preparations, for example, tablets, usually are prepared to make pharmaceutically active ingredients absorb in a digestive organ by disintegration or dissolution through oral administration, without fast disintegration or dissolution in the oral cavity.

15 JP-A-6-502194 (USP 5,464,632) discloses a rapidly disintegrable multiparticulate tablet, the excipient mixture of which is suitable for imparting a disintegration rate such that the tablet disintegrates in the mouth in less than sixty seconds, characterized by the fact that the active substance
20 is present in the form of coated microcrystals or coated or uncoated microgranules. However, there is no disclosure of an acid-labile physiologically active substance with a basic inorganic salt as the active substance, weight percentage of the active substance in the excipient mixture, or the size of
25 the coated microgranule.

 On the other hand, JP-A-5-92918 discloses a powder consisting of a fine-particle core coated with a water-soluble high molecular compound and at least one physiologically active substance, and having a granule size of practically up
30 to 500 μ m. However, there is no disclosure of an acid-labile physiologically active substance with a basic inorganic salt as the physiologically active substance, weight percentage of the active substance in the coated granule or the size of the coated granule.

35 JP-A-63-301816 and USP 5,026,560 disclose spherical

granules having a core coated with spraying powder containing a drug and low substituted hydroxypropylcellulose. However, there is no disclosure of orally disintegrable tablet.

5 EP-A-0452862 discloses a spherical granule obtained by coating a pharmacologically inactive spherical seed core having at least 50 weight % microcrystalline cellulose and an average particle size of 100-1000 μm , with a powder comprising an active ingredient, by using an aqueous binding solution, and spraying an aqueous solution or suspension of a coating agent thereon. However, most of the particle sizes of thus
10 obtained granules are 500 μm or more.

JP-A-1-268627, JP-A-1-268628 and JP-A-8-27033 disclose pharmaceutical compositions using erythritol, respectively. However, there is no disclosure of solid pharmaceutical
15 composition characterized fast disintegration in the oral cavity.

JP-A-9-48726 discloses a buccal formulation consisting of a drug and a substance wetting in a mouldable way on humidifying, and retaining a shape after moulding and drying.
20 As such substance, sugars, sugar alcohols and water-soluble polymers are exemplified.

JP-A-5-271054 discloses production of fast dissolving tablets comprising an active ingredient and sugars.

JP-A-9-71523 discloses a tablet with rapid
25 disintegration in the oral cavity comprising medicine, crystalline cellulose, low-substituted hydroxypropyl cellulose and lubricant.

However, these prior art references nowhere disclose an acid-labile physiologically active substance with a basic
30 inorganic salt as an active substance, weight percentage of the active substance in the tablet or the size of the coated fine granule.

To accompany an aging population and their changes in life environment, it is desired to develop an orally disintegrable
35 solid preparation capable of being administered without water,

retaining the convenience for use which is a characteristic of a tablet, and being administered on demand easily, anytime and anywhere, without water.

Conventional granules have large particle diameters, which results in inferior workability when dispensing, and also results in difficulties in consistently adding a regular amount of the granules when they are combined into tablets or capsules. Granules having a large particle diameter (400 μm or more of average particle diameter) also produce a feeling of roughness in the mouth. Accordingly, especially when used in an orally disintegrable tablet, the average particle diameter of the included granules must be about 400 μm or less, preferably about 350 μm .

For many reasons, such as, masking a bitter taste, or providing enteric abilities or release abilities, it is desirable to prepare the solid pharmaceutical preparations as granules (or fine granules). In particular, in case of granules or fine granules in which the active ingredient of the drug is enteric coated to impart enteric dissolution, there is a need for enteric coating to prevent dissolution by stomach acid (i.e., to make the preparation acid-resistance). It is necessary to coat the whole surface of the particle -before the enteric coating- (including a case of the crystal of physiologically active substance only, and a case of the granule produced by granulation), with the enteric coating.

Namely, at least some uniform thickness (at least 20 μm or more) of the coating layer is needed. Even a portion of thin and weak coating, is undesirable because acid-resistance is lowered. Accordingly, before the enteric coating, it is necessary that the particle is as spherical with smooth surface as possible in form, as uniform as possible in size, and has less cavity.

It is very difficult to produce an enteric coated fine granule with an average particle diameter of 400 μm or less,

when the coating is performed so that at least 20 μm thickness of coating layer may coat the whole particle, and the enteric coated particle contains a basic inorganic salt for stabilization of an acid-labile physiologically active substance, and where it contains binders for maintaining the strength of the particle and/or disintegrants for maintaining the disintegrability (dissolution) of the particles. Further, in the case where the content of the acid-labile physiologically active substance is increased, it is necessary to also increase the content of the excipients such as basic inorganic salt, binders and disintegrants. Furthermore, it is very difficult to produce a small enteric coated fine granule containing the physiologically active substance in high content.

Accordingly, it is desired to develop a fine granule which is coated with the enteric coating layer on the composition containing the physiologically active substance such as a physiologically active substance containing a basic inorganic salt and which has a particle diameter so that roughness or oral discomfort is not felt, to develop a fine granule containing the physiologically active substance, i.e., the active ingredients of drugs, and so forth, in high content, to develop a fine granule keeping enteric dissolution, a disintegrability and dissolution and suitable strength, and to develop an orally disintegrable preparation containing such a fine granule, being a fast disintegration type, showing superior oral disintegrability and dissolution and having suitable strength (hardness) so that it will not be damaged through production processes or handling.

In particular, there is a need to combine an acid-labile physiologically active substance, with basic inorganic salts and so forth for stability, and further to coat with coating layers such as an enteric layer. In such cases, it is an important problem to produce an small enteric coated fine granule, even though it contains the acid-labile

physiologically active substance in high concentration and in high content.

DISCLOSURE OF INVENTION

5 The present invention relates to:

 [1] an orally disintegrable tablet which comprises (i) fine granules having an average particle diameter of 400 μm or less, which fine granules comprise a composition coated by an enteric coating layer, said composition having 10 weight
10 % or more of an acid-labile physiologically active substance and (ii) an additive;

 [2] an orally disintegrable tablet of the above [1], wherein the average particle diameter of the fine granules is 300 to 400 μm ;

15 [3] an orally disintegrable tablet of the above [1], wherein the fine granules further comprise a basic inorganic salt;

 [4] an orally disintegrable tablet of the above [1], wherein the additive comprises a water-soluble sugar alcohol;

20 [5] an orally disintegrable tablet of the above [1], wherein the composition coated by an enteric coating layer is further coated by a coating layer which comprises a water-soluble sugar alcohol;

 [6] an orally disintegrable tablet of the above [4],
25 wherein the additive comprises (i) crystalline cellulose and/or (ii) low-substituted hydroxypropyl cellulose;

 [7] an orally disintegrable tablet of the above [1], wherein the particle diameter of the fine granules is practically 425 μm or less;

30 [8] an orally disintegrable tablet of the above [1], wherein the particle diameter of the fine granules is practically 400 μm or less;

 [9] an orally disintegrable tablet of the above [1], wherein the acid-labile physiologically active substance is
35 a benzimidazole compound or a salt thereof;

[10] an orally disintegrable tablet of the above [9], wherein the benzimidazole compound is lansoprazole;

[11] an orally disintegrable tablet of the above [3], wherein the basic inorganic salt is a salt of magnesium and/or
5 a salt of calcium;

[12] an orally disintegrable tablet of the above [1], wherein the composition comprises a core being coated by a benzimidazole compound and a basic inorganic salt, said core comprising crystalline cellulose and lactose;

10 [13] an orally disintegrable tablet of the above [12], wherein the core comprises 50 weight % or more of lactose;

[14] an orally disintegrable tablet of the above [12], wherein the core comprises 40 to 50 weight % of crystalline cellulose and 50 to 60 weight % of lactose;

15 [15] an orally disintegrable tablet of the above [1], wherein the composition comprises 20 weight % or more of an acid-labile physiologically active substance;

[16] an orally disintegrable tablet of the above [1], wherein the composition comprises 20 to 50 weight % of an
20 acid-labile physiologically active substance;

[17] an orally disintegrable tablet of the above [1], wherein the fine granules are produced by fluidized-bed granulation method;

[18] an orally disintegrable tablet of the above [1], wherein the enteric coating layer comprises an aqueous enteric
25 polymer agent;

[19] an orally disintegrable tablet of the above [18], wherein the aqueous enteric polymer agent is a methacrylate copolymer;

30 [20] an orally disintegrable tablet of the above [18], wherein the enteric coating layer further comprises a sustained-release agent;

[21] an orally disintegrable tablet of the above [20], wherein the sustained-release agent is a methacrylate
35 copolymer;

[22] an orally disintegrable tablet of the above [20], wherein the sustained-release agent is in an amount of 5 to 15 weight % relative to 100 weight % of the aqueous enteric polymer agent;

5 [23] an orally disintegrable tablet of the above [4], wherein the water-soluble sugar alcohol is erythritol;

[24] an orally disintegrable tablet of the above [4], wherein the water-soluble sugar alcohol is mannitol;

10 [25] an orally disintegrable tablet of the above [5], wherein the water-soluble sugar alcohol is in an amount of 5 to 97 weight % relative to 100 weight % of the orally disintegrable tablet apart from the fine granules;

15 [26] an orally disintegrable tablet of the above [4], wherein the crystalline cellulose is in an amount of 3 to 50 weight % relative to 100 weight % of the tablet apart from the fine granule;

[27] an orally disintegrable tablet of the above [6], wherein the content of hydroxypropoxyl group in the low-substituted hydroxypropyl cellulose is 7.0 to 9.9 weight %;

20 [28] an orally disintegrable tablet of the above [6], wherein the content of hydroxypropoxyl group in the low-substituted hydroxypropyl cellulose is 5.0 to 7.0 weight %;

[29] an orally disintegrable tablet of the above [1], which further comprises crospovidone;

25 [30] an orally disintegrable tablet of the above [1], wherein the oral disintegration time is one minute or less;

[31] an orally disintegrable tablet of the above [1], which comprises no lubricant inside the tablet;

30 [32] fine granules having an average particle diameter of 400 μm or less, which comprise a composition coated by an enteric coating layer, said composition having (i) 25 weight % or more of an acid-labile physiologically active substance and (ii) a basic inorganic salt;

35 [33] fine granules of the above [32], wherein the average particle diameter of the fine granules is 300 to 400 μm ;

[34] fine granules of the above [32], wherein the particle diameter of the fine granules is practically 425 μm or less;

5 [35] fine granules of the above [32], wherein the particle diameter of the fine granules is practically 400 μm or less;

[36] fine granules of the above [32], wherein the acid-labile physiologically active substance is a benzimidazole compound or a salt thereof;

10 [37] fine granules of the above [36], wherein the benzimidazole compound is lansoprazole;

[38] fine granules of the above [32], wherein the basic inorganic salt is a salt of magnesium and/or a salt of calcium;

15 [39] fine granules of the above [32], wherein the composition comprises a core being coated by a benzimidazole compound and a basic inorganic salt, said core comprising crystalline cellulose and lactose;

[40] fine granules of the above [39], wherein the core comprises 50 weight % or more of lactose;

20 [41] fine granules of the above [32], wherein the composition comprises 25 to 40 weight % of an acid-labile physiologically active substance;

[42] fine granules of the above [32], which are produced by fluidized-bed granulation method;

25 [43] fine granules of the above [32], wherein the enteric coating layer comprises an aqueous enteric polymer agent;

[44] fine granules of the above [43], wherein the aqueous enteric polymer agent is a methacrylate copolymer;

30 [45] fine granules of the above [43], wherein the enteric coating layer further comprise a sustained-release agent;

[46] fine granules of the above [45], wherein the sustained-release agent is a methacrylate copolymer;

35 [47] fine granules of the above [45], wherein the sustained-release agent is in an amount of 5 to 15 weight % relative to 100 weight % of the aqueous enteric polymer agent;

[48] fine granules of the above [32], wherein the enteric coating layer is in an amount of 50 to 70 weight % relative to 100 weight % of the fine granules;

[49] a tablet, granule, fine granule, capsule,
5 effervescent or suspension preparation which comprises the fine granules of the above [32], and so forth.

In the present specification, "coating" means also partial coating and adhesion or adsorption in addition to
10 coating the whole surface of an object (e.g., core) which is to be coated.

"Spherical" means also forms having a curved surface such as forms having elliptic cross sections, and forms in the shapes of eggplants and drops in addition to spheres.

15 "Average particle diameter" means volume based distribution median diameter (median diameter: 50% particle diameter from cumulative distribution), unless otherwise specified. It can be measured by, for example, a laser diffraction particle distribution measurement method.
20 Concretely exemplified is a method using Raser Diffraction Analyzer, type: HEROS RODOS [trade name; manufactured by Sympatec (Germany)].

"An orally disintegrable tablet" of the present invention
25 comprises (i) fine granules having an average particle diameter of 400 μm or less, which fine granules comprise a composition coated by an enteric coating layer, said composition having 10 weight % or more of an acid-labile physiologically active substance and (ii) an additive.

30 In the present invention, "fine granules having an average particle diameter of 400 μm or less, which fine granules comprise a composition coated by an enteric coating layer, said composition having 10 weight % or more of an acid-labile physiologically active substance" have an average particle
35 diameter of about 400 μm or less, in order that roughness is


not felt in the mouth. Preferably, the average particle diameter of the fine granules is 300 to 400 μm .

Aside from the average particle diameter of the above "fine granules", regarding the maximum particle size, the particle diameter is practically 425 μm or less, and preferably practically 400 μm or less. Preferably, the particle diameter is practically 300 to 425 μm , more preferably 300 to 400 μm .

"Practically" as used in "the particle diameter is practically 425 μm or less" and "the particle diameter is practically 400 μm or less" means that the particles may include a small quantity (about 5 weight % or less) of particles whose particle diameter is out of above described range, to include the inevitably contaminant particles.

"An acid-labile physiologically active substance" includes a compound being unstable in an acidic region and/or a compound inactivated by an acid, especially a pharmaceutical ingredient. Concretely mentioned are vitamins such as vitamin B₁₂, fursultiamine, folic acid, vitamin A, vitamin D, as well as a known benzimidazole compound having an antiulcer activity of the formula (I) below, or a salt thereof.

Formula (I):



wherein ring A may be substituted; R¹, R³ and R⁴ are the same or different and each is a hydrogen, an alkyl or an alkoxy; R² is C₁₋₄ alkyl which may be substituted by a substituent(s) selected from the group consisting of halogen, hydroxy and C₁₋₄ alkoxy; and n is 0 or 1.

In the above formula (I), "substituent(s)" of the "substituted ring A" include, for example, halogen, C₁₋₁₀ alkyl which may be substituted, C₃₋₇ cycloalkyl which may be substituted, C₂₋₁₆ alkenyl which may be substituted, C₁₋₁₀ alkoxy which may be substituted, cyano, carboxy, C₁₋₇ alkoxycarbonyl, C₁₋₄ alkoxycarbonyl-C₁₋₄ alkyl, carbamoyl, carbamoyl-C₁₋₄ alkyl, hydroxy, hydroxy-C₁₋₇ alkyl, C₁₋₆ acyl, carbamoyloxy, nitro, C₂₋₆ acyloxy, C₆₋₁₂ aryl, C₆₋₁₂ aryloxy, C₁₋₆ alkylthio, C₁₋₆ alkylsulfinyl, etc.

10 The "substituent" of the above "C₁₋₁₀ alkyl which may be substituted", "C₃₋₇ cycloalkyl which may be substituted", or "C₂₋₁₆ alkenyl which may be substituted" includes, for example, (1) halogen, (2) nitro, (3) amino which may be substituted by 1 or 2 of C₁₋₄ alkyl and C₁₋₄ acyl, etc., (4) 15 amidino, (5) guanidino, (6) carbamoyl, etc. The number of these substituent is 1 to 3.

The "substituent" of the above "C₁₋₁₀ alkoxy which may be substituted" includes, for example, (1) halogen, (2) nitro, (3) amino which may be substituted by 1 or 2 of C₁₋₄ alkyl and 20 C₁₋₄ acyl, etc., (4) amidino, (5) guanidino, etc. The number of these substituent is 1 to 3.

The above "C₁₋₆ acyl" includes, for example, C₂₋₆ alkanoyl such as formyl, acetyl, propionyl, etc.

The above "C₁₋₄ acyl" includes, for example, formyl and 25 C₂₋₄ alkanoyl such as acetyl, propionyl, etc.

The above "C₂₋₆ acyloxy" includes, for example, C₂₋₆ alkanoyloxy such as acetyloxy, etc.

The above "C₆₋₁₂ aryl" includes, for example, phenyl, naphthyl, etc.

30 The above "C₆₋₁₂ aryloxy" includes, for example, phenoxy, naphthyloxy, etc.

The "alkyl" for R^1 , R^3 or R^4 includes, for example, a straight-chain or branched C_{1-10} alkyl such as methyl, ethyl, n-propyl, isopropyl, n-butyl, isobutyl, sec-butyl, tert-butyl, n-pentyl, isopentyl, neopentyl, hexyl, heptyl, octyl, nonyl, decyl, etc. Among others, preferred is a straight-chain or branched C_{1-6} alkyl. More preferred is a straight-chain or branched C_{1-3} alkyl.

The "alkoxy" for R^1 , R^3 or R^4 includes, for example, C_{1-10} alkoxy such as methoxy, ethoxy, n-propoxy, isopropoxy, n-butoxy, isobutoxy, sec-butoxy, tert-butoxy, n-pentoxo, isopentoxo, neopentoxo, hexyloxy, heptyloxy, octyloxy, nonyloxy, cyclobutoxy, cyclopentoxo, cyclohexyloxy, etc. Among others, preferred is C_{1-6} alkoxy. More preferred is C_{1-3} alkoxy.

The " C_{1-4} alkyl" of the " C_{1-4} alkyl which may be substituted by a substituent(s) selected from the group consisting of halogen, hydroxy and C_{1-4} alkoxy" for R^2 includes, for example, methyl, ethyl, n-propyl, isopropyl, n-butyl, isobutyl, sec-butyl, tert-butyl, etc.

The " C_{1-4} alkoxy" of the above " C_{1-4} alkyl which may be substituted by a C_{1-4} alkoxy" includes, for example, methoxy, ethoxy, n-propoxy, isopropoxy, n-butoxy, isobutoxy, sec-butoxy, tert-butoxy, etc.

The number of the substituents which the " C_{1-4} alkyl" has is preferably 1 to 3.

Salts of the benzimidazole compound include pharmaceutically acceptable salts such as alkali metal salts, e. g., sodium salts and potassium salts, alkaline earth metal salts e. g., calcium salts and magnesium salts, etc.

Such benzimidazole compounds having an antiulcer

activity, or salts thereof include, for example, a compound or a salt thereof disclosed in JP-A-52-62275, JP-A-54-141783, JP-A-57-53406, JP-A-58-135881, JP-A-58-192880, JP-A-59-181277, JP-A-61-50978, JP-A-62-116576, JP-A-62-277322, JP-A-62-258320, JP-A-62-258316, JP-A-64-6270, JP-A-64-79177, JP-A-5-59043, JP-A-62-111980, JP-A-5-117268, EP-A-166287, EP-A-519365, and so forth.

The "physiologically active substance" of the present invention preferably is a benzimidazole compound or a salt thereof such as lansoprazole, omeprazole, rabeprazole, pantoprazole, perprazole, leminoprazole, TU-199, etc. Preferred is lansoprazole and omeprazole, etc. More preferred is lansoprazole.

15

The amount of the "acid-labile physiologically active substance" in the "composition" is, for example, about 10 weight % or more, preferably about 20 weight % or more, more preferably about 23 weight % or more, especially preferably about 25 weight % or more. Among others, preferred is 20 to 50 weight %.

20

In the "composition", a basic inorganic salt is preferably incorporated with the acid-labile physiologically active substance.

25

The "basic inorganic salt" includes, for example, a basic inorganic salt of sodium, potassium, magnesium and/or calcium, preferably a basic inorganic salt of magnesium and/or calcium.

Among others, preferred is a basic inorganic salt of magnesium.

30

The basic inorganic salt of sodium includes, for example, sodium carbonate, sodium hydrogencarbonate, etc.

35

The basic inorganic salt of potassium includes, for example, potassium carbonate, potassium hydrogencarbonate, etc.

The basic inorganic salt of magnesium includes, for example, heavy magnesium carbonate, magnesium carbonate, magnesium oxide, magnesium hydroxide, magnesium metasilicate aluminate, magnesium silicate, magnesium aluminate, synthetic hydrotalcite $[\text{Mg}_6\text{Al}_2(\text{OH})_{16}\cdot\text{CO}_3\cdot 4\text{H}_2\text{O}]$, aluminum magnesium hydroxide $[2.5\text{MgO}\cdot\text{Al}_2\text{O}_3\cdot x\text{H}_2\text{O}]$, etc. Among others, preferred is heavy magnesium carbonate, magnesium carbonate, magnesium oxide, magnesium hydroxide, etc.

The basic inorganic salt of calcium includes, for example, precipitated calcium carbonate, calcium hydroxide, etc.

The preferable examples of the "basic inorganic salt" include heavy magnesium carbonate, magnesium carbonate, magnesium oxide, magnesium hydroxide, etc.

Such basic inorganic salt of magnesium or calcium, etc. has a basic pH (not less than 7) when it is in the form of a 1 % aqueous solution or suspension.

Two or more of these basic inorganic salts (preferably a basic inorganic salt of magnesium, a basic inorganic salt of calcium, etc.) can be used as a mixture in a given ratio.

The amount of the basic inorganic salt to be used is appropriately selected depending on the kind of the basic inorganic salt and is, for instance, about 0.3 to 200 weight %, preferably about 1 to 100 weight %, more preferably about 10 to 50 weight %, especially preferably about 20 to 40 weight % relative to the benzimidazole compound or a salt thereof.

The "composition" may contain water-soluble polymers, the following binders, lubricants, and excipients, etc. in common use as pharmaceutical materials. The amount of such water-soluble polymers, binders, lubricants, and excipients is selected from amounts commonly employed in the manufacture of preparations in general dosage forms.

The "water-soluble polymer" includes, for example, a water-soluble polymer which is soluble in ethanol (i.e., an

ethanol-soluble water-soluble polymer) such as a cellulose derivative (e.g., hydroxypropyl cellulose, which may be referred to as "HPC" hereinafter), poly(vinylpyrrolidone), etc.; a water-soluble polymer which is insoluble in ethanol (i.e., an ethanol-insoluble water-soluble polymer) such as a cellulose derivative (e.g., hydroxypropylmethyl cellulose, which may be referred to as "HPMC" hereinafter, methyl cellulose, carboxymethyl cellulose sodium, etc.), sodium polyacrylate, polyvinyl alcohol, sodium alginate, and guar gum, etc.

When such water-soluble polymers are used, the dissolution of drugs (physiologically active substances) can be controlled by employing them in combination with the ethanol-soluble water-soluble polymer and ethanol-insoluble water-soluble polymer or by employing them in combination with some water-soluble polymers having different viscosity.

In the present invention, the "water-soluble polymer" is preferably, a cellulose derivative such as HPC, HPMC, and methyl cellulose, and polyvinyl alcohol. More preferred is a cellulose derivative such as HPC, HPMC.

The "HPC" contains, for example, about 53.4 to 77.5 weight %, more preferably about 60 to 70 weight %, of hydroxypropoxyl group. The viscosity of 2 weight % aqueous solution of HPC at 20 °C is usually about 1 to 150,000 cps (centipoise). As the above HPC, hydroxypropyl cellulose defined in Japanese Pharmacopoeia may be employed. Hereinafter, all viscosity of HPC is a value of 2 weight % aqueous solution at 20 °C.

The "HPMC" is a mixed ether which is connected by a methoxy group and a hydroxypropoxy group. The content of the methoxy group of HPMC is, for example, about 19 to 30 weight %. The content of the hydroxypropoxy group is, for example, about 4 to 12 weight %. The viscosity of 2 weight % aqueous solution of HPMC at 20 °C is usually about 1 to 40,000 centistokes. As such HPMC may be employed hydroxypropylmethyl cellulose 2208 defined by Japanese Pharmacopoeia, hydroxypropylmethyl

cellulose 2906 defined by Japanese Pharmacopoeia, hydroxypropylmethyl cellulose 2910 defined by Japanese Pharmacopoeia, and so forth. Hydroxypropyl cellulose(s) may be employed alone or in admixture of two or more thereof.

5 The content of the water-soluble polymer such as HPC and/or HPMC is usually about 0.1 to 50 weight %, preferably about 1 to 30 weight %, as against the whole "composition" containing the physiologically active substance, in order to control the dissolution of the physiologically active
10 substance in the composition containing the physiologically active substance and retain a high content of the physiologically active substance.

 The above "enteric coating layer" which coats the
15 "composition having 10 weight % or more of an acid-labile physiologically active substance" includes, for example, an aqueous enteric polymer agent such as cellulose acetate phthalate (CAP), hydroxypropylmethyl cellulose phthalate (hereinafter, referred to as HP-55), hydroxymethyl cellulose
20 acetate succinate, methacrylate copolymer [e.g., Eudragit L30D-55 etc. (trade name; manufactured by Rohm GmbH (Germany)), KollICOat MAE30DP (trade name; manufactured by BASF (Germany)), Polyquid PA-30 (trade name; manufactured by SanyoKasei (Japan)), etc.], carboxymethyl cellulose, shellac,
25 etc.; a sustained-release agent such as methacrylate copolymer [e.g., Eudragit NE30D (trade name), Eudragit RL30D (trade name), Eudragit RS30D (trade name), etc.]; a water-soluble polymer; plasticizers such as triethyl citrate, polyethylene glycol, acetylated monoglyceride, triacetin, castor oil, etc.
30 and mixtures thereof.

 The "aqueous enteric polymer agent" is preferably a methacrylate copolymer. The "sustained-release agent" is preferably a methacrylate copolymer.

 The "sustained-release agent" is used in an amount of 5
35 to 30 weight %, preferably 5 to 15 weight %, relative to 100

weight % of the "aqueous enteric polymer agent". The "plasticizers" is used in an amount of 5 to 30 weight % relative to 100 weight % of the "aqueous enteric polymer agent".

5 The "additives" of the "orally disintegrable tablet which comprises (i) fine granules having an average particle diameter of 400 μ m or less, which fine granules comprise a composition coated by an enteric coating layer, said composition having 10 weight % or more of an acid-labile
10 physiologically active substance and (ii) an additive" may be ones commonly employed as pharmaceutical materials. The amount of such additives to be used is selected from amounts commonly employed in the manufacture of preparations in general dosage forms.

15 The "additives" include, for example, a water-soluble sugar alcohol, a crystalline cellulose, a low-substituted hydroxypropyl cellulose, as well as, binders, acids, foaming agents, artificial sweeteners, flavorants, lubricants, colorants, stabilizers, excipients, disintegrants, and so
20 forth.

 The "water-soluble sugar alcohol" means a water-soluble sugar alcohol which needs water in an amount of less than 30 ml when 1 g of water-soluble sugar alcohol is added to water and dissolved within about 30 minutes at 20 °C by strongly
25 shaking every 5 minutes for 30 seconds.

 The "water-soluble sugar alcohol" includes, for example, sorbitol, mannitol, maltitol, reduced starch saccharide, xylitol, reduced paratinose, erythritol, etc. Two or more of these water-soluble sugar alcohols can be used as a mixture
30 in a given ratio.

 The "water-soluble sugar alcohol" is preferably mannitol, xylitol and erythritol. More preferred is mannitol and erythritol. Especially preferred is mannitol. As erythritol, one that is produced by fermentation with yeasts
35 using glucose as the starting material, and that has a particle

size of at most 50 mesh is used. Such erythritol is available on the market, e.g. as manufactured by Nikken Chemical Co., Ltd. (Japan).

5 The "water-soluble sugar alcohol" is usually employed in an amount of about 5 to 97 weight %, preferably about 10 to 90 weight % relative to 100 weight % of the orally disintegrable tablet apart from the fine granules, in order to obtain sufficient strength of the preparation and sufficient disintegration or dissolution in the oral cavity.

10 For example, mannitol or erythritol is usually employed in an amount of about 5 to 90 weight %, preferably about 10 to 80 weight %, more preferably about 20 to 80 weight %, especially preferably about 50 to 80 weight % relative to 100 weight % of the orally disintegrable tablet apart from the fine granules.

15 The "crystalline cellulose" includes refined one having partially α -cellulose depolymerization. Such crystalline cellulose includes one called microcrystalline cellulose.

20 Examples of the "crystalline cellulose" include CEOLUS KG801, avicel PH101, avicel PH102, avicel PH301, avicel PH302, avicel RC-591 (crystalline cellulose carmellose sodium), etc. Among these, preferably employed is CEOLUS KG801 which is also called crystalline cellulose of high compressibility. Two or more of the crystalline cellulose can be used as a mixture in a given ratio. Such crystalline cellulose is available on the market, for example, as manufactured by Asahi Chemical Co., Ltd. (Japan).

25 The "crystalline cellulose" is used, for instance, in an amount of about 3 to 50 weight %, preferably about 5 to 40 weight %, more preferably about 5 to 20 weight % relative to 100 weight % of the orally disintegrable tablet apart from the fine granules.

35 The "low-substituted hydroxypropyl cellulose" means a low-substituted hydroxypropyl cellulose wherein the content of hydroxypropoxyl group in the hydroxypropyl cellulose

(hereinafter, may be abbreviated to "the content of HPC group") is about 5.0 to 9.9 weight %, preferably a low-substituted hydroxypropyl cellulose wherein the content of HPC group is about 5.0 to 7.0 weight %, a low-substituted hydroxypropyl cellulose wherein the content of HPC group is about 7.0 to 9.9 weight %, and so forth.

The "low-substituted hydroxypropyl cellulose wherein the content of HPC group is about 7.0 to 9.9 % includes, for example, LH-22, LH-32 and mixtures thereof, which are commercially available [Shin-Etsu Chemical Co., Ltd. (Japan)]. Also, they can be produced in accordance with *per se* known methods, for example, methods described in JP-B-82 53100 or analogous thereto.

The low-substituted hydroxypropyl cellulose wherein the content of HPC group is about 5.0 to 7.0 % includes, for example, LH-23, LH-33 and mixtures thereof, described in the following Reference Examples. They can be produced in accordance with *per se* known methods, for example, methods described in JP-B-82 53100 or analogous thereto.

At first, alkaline cellulose containing free alkaline and propylene oxide is reacted to obtain the crude low-substituted hydroxypropyl cellulose containing free alkaline.

Concretely, for example, raw material pulp such as wood pulp and cotton leader is immersed in about 10 to 50 % concentration of an aqueous solution of sodium hydroxide, and pressed to obtain alkaline cellulose of which NaOH/cellulose ratio is about 0.1 to 1.2 (ratio by weight). Next, crude low-substituted hydroxypropyl cellulose containing free alkaline is obtained by reacting the resulting alkaline cellulose and propylene oxide with stirring at about 20 to 90 °C for about 2 to 8 hours. Propylene oxide is used in an amount so that the content of hydroxypropoxyl group in the desired low-substituted hydroxypropyl cellulose can be 5 or more weight % to less than 7 weight % (in case of the low-substituted hydroxypropyl cellulose wherein the content of HPC group is

about 5.0 to 7.0 weight %), 7 or more weight % to less than 9.9 weight % (in case of the low-substituted hydroxypropyl cellulose wherein the content of HPC group is about 7.0 to 9.9 weight %).

5 The crude low-substituted hydroxypropyl cellulose containing free alkaline is dispersed in water or hot water containing about 5 to 80 % of acid necessary to neutralize all the alkaline, and a part of the crude low-substituted hydroxypropyl cellulose containing free alkaline is dissolved
10 therein. Acid is further added to neutralize the remaining alkaline.

 After the neutralization, some processes such as drainage, drying and grinding are performed in accordance with conventional methods to obtain the desired low-substituted
15 hydroxypropyl cellulose.

 The particle diameter of "the low-substituted hydroxypropyl celluloses wherein the content of hydroxypropoxyl group is 5.0 to 7.0 weight %" to be used in the present invention is, for example, about 5 to 60 μm ,
20 preferably about 10 to 40 μm , as a average particle diameter.

 In the above ranges, in case that low-substituted hydroxypropyl celluloses (L-HPC) having a relatively large particle diameter (for example, L-HPC having about 26 to 40 μm of the average particle diameter) is employed, a
25 pharmaceutical preparation superior in disintegrability can be produced. On the other hand, in case that L-HPC having a relatively small particle diameter (for example, L-HPC having about 10 to 25 μm of the average particle diameter) is employed, a pharmaceutical preparation superior in strength of the
30 preparation can be produced. Accordingly, the particle diameter of L-HPC can be suitably selected according to the characteristics of the desired pharmaceutical preparation.

 The "low-substituted hydroxypropyl cellulose wherein the content of HPC group is 5.0 to 7.0 weight %" or the "low-
35 substituted hydroxypropyl cellulose wherein the content of HPC

group is 7.0 to 9.9 %" is usually employed in an amount of about 3 to 50 weight %, preferably about 5 to 40 weight %, relative to 100 weight % of the orally disintegrable tablet apart from the fine granules, in order to obtain sufficient oral
5 disintegrability and sufficient strength of the preparation.

The "binders" include, for example, hydroxypropyl cellulose, hydroxypropylmethylcellulose, crystalline cellulose, α starch (pregelatinized starch), polyvinylpyrrolidone, gum arabic powder, gelatin, pullulan,
10 low-substituted hydroxypropyl cellulose, etc. The use of crystalline cellulose as the binders provides a solid preparation which exhibits more excellent strength of a preparation while retaining excellent disintegration and dissolution in the oral cavity.

15 The "acids" include, for example, citric acid (e.g., citric acid anhydrous), tartaric acid, malic acid, etc.

The "foaming agents" include, for example, sodium hydrogen carbonate, etc.

20 The "artificial sweeteners" include, for example, saccharin sodium, dipotassium glycyrrhizinate, aspartame, stevia, thaumatin, etc.

The "flavorants" include synthetic flavorants or natural flavorants, such as lemon, lime, orange, menthol, strawberry, etc.

25 The "lubricants" include, for example, magnesium stearate, sucrose fatty acid ester, polyethyleneglycol, talc, stearic acid, etc.

30 The "colorants" include, for example, various food colorants such as Food Yellow No. 5, Food RED No.2, Food Blue No.2, etc., food lakes, red iron oxide, etc.

The "stabilizers" include, for example, the above-mentioned "basic inorganic salt".

35 The "excipients" include, for example, lactose, sucrose, D-mannitol, starch, corn starch, crystalline cellulose, light silicic anhydride, titanium oxide, etc.

The "disintegrants" include those conventionally used in the pharmaceutical field, such as (1) crospovidone, (2) super disintegrants such as croscarmellose sodium [FMC-Asahi Chemical Co., Ltd. (Japan)], carmellose calcium [Gotoku Chemical(Yakuhin), (Japan)], (3) carboxymethylstarch sodium [e.g., Matsutani Chemical Co., Ltd. (Japan)], (4) low-substituted hydroxypropyl cellulose [e.g., Shin-Etsu Chemical Co., Ltd. (Japan)], (5) corn starch, etc. Among others, preferred is, for example, crospovidone.

The "crospovidone" includes polyvinylpolypyrrolidone (PVPP), 1-vinyl-2-pyrrolidinone homopolymer, 1-ethenyl-2-pyrrolidinone homopolymer, etc, such as Kollidon CL [manufactured by BASF (Germany)], Polyplasdone XL [manufactured by ISP Ltd. (Japan)], Polyplasdone XL-10 [manufactured by ISP Ltd. (Japan)], Polyplasdone INF-10 [manufactured by ISP Ltd. (Japan)], etc. Usually crospovidone having a molecular weight of at least 1,000,000 is used.

Two or more of these disintegrants can be as a mixture in a given ratio. For example, (i) crospovidone solely, or (ii) crospovidone and another disintegrant(s) is preferably employed.

The "disintegrants" are used, for instance, in an amount of about 1 to 15 weight %, preferably about 1 to 10 weight %, more preferably about 3 to 7 weight %, relative to 100 weight % of the orally disintegrable tablet apart from the fine granules.

In the present invention, the "fine granules" may contain, for example, titanium oxide as a masking agent.

The diameter of the "orally disintegrable tablet" of the present invention is about 5 to 20 mm, preferably about 7 to 15 mm, more preferably about 8 to 13 mm.

The "orally disintegrable tablet" may comprise no lubricant inside the tablet.

The "orally disintegrable tablet" of the present invention exhibits fast disintegrability or dissolubility in

the oral cavity, and also an appropriate strength of preparation.

5 The oral disintegration time of the "orally disintegrable tablet" of the present invention (the time for healthy male or female adults to complete disintegration by buccal saliva) is one minute or less, usually about 50 seconds or less, preferably about 40 seconds or less, more preferably about 30 seconds or less.

10 The strength of the "orally disintegrable tablet" of the present invention (measurement with a tablet hardness tester) is usually about 1 to 20 kg, preferably about 2 to 15 kg, more preferably 3 to 8 kg.

15 In the above-mentioned fine granules, "fine granules having an average particle diameter of 400 μ m or less, which comprise a composition coated by an enteric coating layer, said composition having (i) 25 weight % or more of an acid-labile physiologically active substance and (ii) a basic inorganic salt" are novel.

20 The "fine granules" have an average particle diameter of about 400 μ m or less, preferably 350 μ m or less. Preferably, the average particle diameter of the fine granules is 300 to 400 μ m. Aside from the average particle diameter of the "fine granules", regarding the maximum particle size, the particle diameter is practically 425 μ m or less, and preferably
25 practically 400 μ m or less. Preferably, the particle diameter is practically 300 to 400 μ m or less.

30 Regarding the fine granule of the present invention, the dissolution of the physiologically active substance can be controlled by formulating the coat (coating layer) to have different viscosity or content of the water-soluble polymer (e.g., HPC, HPMC and so forth) or by formulating the coat to have a controlled ratio of the ethanol-soluble water-soluble polymer (e.g., HPC) and the ethanol-insoluble water-soluble polymer (e.g., HPMC). The dissolution of the physiologically

active substance is not very influenced by liquidity, which can be suitably controlled.

As a pharmaceutical preparation which comprises the "fine granules" of the present invention, there may be employed, for example a solid preparation such as tablet, granule, fine granule, capsule, effervescent, etc; a liquid preparation such as suspension preparation, etc. Among others, preferred is a tablet, more preferred is an orally disintegrable tablet.

When the "fine granule" of the present invention is used for a tablet except for an orally disintegrable tablet, the diameter of the tablet is about 5 to 10 mm, preferably about 5 to 8 mm. When the fine granule of the present invention is used for a capsule, the size of the capsule is preferably a #2 capsule or less.

The "orally disintegrable tablet" of the present invention and the "pharmaceutical preparation which comprises the fine granules of the present invention" may contain a foaming component to impart a refreshing feeling at administration.

Also, with an effervescent comprising the foaming component, the dissolution can be precisely controlled compared to the case of a fine granule alone. As the foaming component, various compounds can be employed as long as safety is not interfered with. Examples of the foaming component include alkaline metal carbonate (e.g., sodium carbonate, potassium carbonate, etc.), alkaline metal hydrogencarbonate (e.g., sodium hydrogencarbonate, potassium hydrogencarbonate, etc.) and ammonium carbonate and so forth. The foaming component(s) may be employed alone or in an admixture of two or more thereof.

The preferable foaming component includes sodium carbonate, sodium hydrogencarbonate, ammonium carbonate and so forth.

The ratio of the foaming component can be selected within the range in which it is possible to impart the foam, for example, about 10 to 2500 weight %, preferably about 50 to 2000 weight

% (e.g., about 75 to 1500 weight %), more preferably about 100 to 1000 weight %, relative to 100 weight % of the fine granule.

In employing the effervescent and the fine granule having small particle diameter, it is advantageous to quickly prepare a homogeneous aqueous solution or suspension, and to maintain the dispersed condition. But, in case that the particle diameter is too small, the problem tends to occur that the fine granule adheres to the wall of machine by static electricity during production processes.

The specific volume of the above fine granule is about 3 ml/g or less, preferably about 2 ml/g or less. In order to maintain the homogeneous condition of the fine granule in the suspension obtained by adding the foaming agent composition, the specific volume can be suitably selected in the above range according to the specific gravity (specific volume) of the dispersion medium.

The "composition" in the present invention can be produced by a known granulation method.

The "granulation method" includes, for example, rolling granulation method (e.g., centrifugal rolling granulation, etc.), fluidized-bed granulation (e.g., rolling fluidized-bed granulation, fluidized granulation, etc.), stirring granulation and so forth. Among others, preferred is fluidized-bed granulation method, more preferred is rolling fluidized-bed granulation method.

Concrete example of the "rolling granulation method" includes a method using "CF apparatus" manufactured by Freund Industrial Co., Ltd. (Japan) and so forth. Concrete examples of the "rolling fluidized-bed granulation method" include methods using "SPIR-A-FLOW", "multi plex" manufactured by Powrex Corp. (U. S. A.), "New-Marumerizer" manufactured by Fuji Paudal Co., Ltd. (Japan), and so forth. The method for spraying the mixture can be suitably selected in accordance with the kind of granulator, and may be, for example, any one

of a top spray method, a bottom spray method, a tangential spray method, and so forth. Among others, a tangential spray method is preferred.

5 The "composition" in the present invention can be produced in accordance with, for example, a method which comprises coating a core comprising crystalline cellulose and lactose with an acid-labile physiologically active substance.

For example, employed is a method described in JP-A-5-92918 (coating method), which comprises coating a core
10 comprising crystalline cellulose and lactose with an acid-labile physiologically active substance, if necessary together with a basic inorganic salt, binders, lubricants, excipients, a water-soluble polymer, etc. (hereinafter, may be abbreviated to "coating layer"). For example, employed is
15 a method which comprises coating a core with an acid-labile physiologically active substance and a basic inorganic salt, and then further with binders, lubricants, excipients, a water-soluble polymer, etc.

The average particle diameter of the "cores" is about 250
20 μm or less, preferably about 50 to 250 μm , more preferably about 100 to 250 μm , especially preferably about 100 to 200 μm . The "cores" having the above average particle diameter include particles which all pass through a #50 sieve (300 μm), particles where about 5 w/w % or less of the total remain on a #60 sieve
25 (250 μm), and particles where about 10 w/w % or less of the total pass through a #282 sieve (53 μm). The specific volume of the "core" is about 5 ml/g or less, preferably about 3 ml/g or less.

Examples of the "core" include
30 (1) a spherical granulated product comprising crystalline cellulose and lactose, (2) a spherical granulated product being about 150 to 250 μm and comprising crystalline cellulose (avicel SP, manufactured by Asahi Chemical Co., Ltd. (Japan)),
(3) a stirring granulated product being about 50 to 250 μm and

comprising lactose (9 parts) and α starch (1 part), (4) a micro particle being about 250 μ m or less classified as a spherical granule comprising micro crystalline cellulose described in JP-A-61-213201, (5) a processed product such as wax formed to a sphere by spraying or melting granulation, (6) a processed product such as gelatin beads comprising oil component, (7) calcium silicate, (8) starch, (9) a porous particle such as chitin, cellulose, chitosan, etc, and (10) a bulk product such as granulated sugar, crystalline lactose or sodium chloride, and processed preparations thereof. Further, these cores may be produced in accordance with per se known grinding method or granulation method, and sifted to prepare the particles having the desired particle diameter.

The above "spherical granulated product comprising crystalline cellulose and lactose" includes, for example (i) a spherical granulated product being 100 to 200 μ m and comprising crystalline cellulose (3 parts) and lactose (7 parts) [e.g., Nonpareil 105 (70-140) (particle diameter of 100 to 200 μ m), manufactured by Freund Industrial Co., Ltd. (Japan)], (ii) a spherical granulated product being about 150 to 250 μ m and comprising crystalline cellulose (3 parts) and lactose (7 parts) [e.g., Nonpareil NP-7:3, manufactured by Freund Industrial Co., Ltd. (Japan)], (iii) a spherical granulated product being 100 to 200 μ m and comprising crystalline cellulose (4.5 parts) and lactose (5.5 parts) [e.g., Nonpareil 105T (70-140) (particle diameter of 100 to 200 μ m), manufactured by Freund Industrial Co., Ltd. (Japan)], (iv) a spherical granulated product being about 150 to 250 μ m and comprising crystalline cellulose (5 parts) and lactose (5 parts) [e.g., Nonpareil NP-5:5, manufactured by Freund Industrial Co., Ltd. (Japan)], and so forth.

In order to produce a pharmaceutical preparation which is superior in dissolution while retaining suitable strength, the "core" includes, for example, preferably the spherical

granulated product comprising crystalline cellulose and lactose, more preferably the spherical granulated material comprising crystalline cellulose and lactose and containing 50 weight % or more of lactose. Among others, preferred is
5 a core comprising 40 to 50 weight % of crystalline cellulose and 50 to 60 weight % of lactose.

As the "core" employed in the present invention, in particular, there may be employed the spherical granulated product comprising crystalline cellulose and lactose, more
10 preferably the spherical granulated product with a diameter of about 100 to 200 μm and comprising crystalline cellulose (4.5 parts) and lactose (5.5 parts).

The "core" may contain the physiologically active substance such as the above described pharmaceutical
15 ingredient. Also, the "core" may not contain the physiologically active substance because the release of the physiologically active substance can be controlled by a coating layer containing the physiologically active substance.

20 The "core" is preferably as uniform a sphere as possible, for reducing the irregularity of the coating, in addition to being a powdery core.

The ratio of the "coating layer" to the "core" can be selected within the range in which it is possible to control
25 dissolution of the physiologically active substance and particle size of the composition, for example, usually about 50 to 400 weight % relative to 100 weight % of the core.

The coating layer may be constructed by plural layers. At least one layer of the plural layers must contain the
30 physiologically active substance. The combination of various layers such as a coating layer not containing the active ingredient, a base coating layer, and an enteric coating layer which constitute the coating layer can be suitably selected.

In case that the "core" is coated, for example, the above
35 physiologically active substance and the water-soluble

polymer can be employed in admixture thereof. The admixture may be a solution or a dispersion, and can be prepared by using an organic solvent such as water or ethanol or an admixture thereof.

5 The concentration of the water-soluble polymer in the admixture varies according to the ratio of the physiologically active substance and the excipients, and is usually about 0.1 to 50 weight %, preferably about 0.5 to 10 weight %, in order to retain the binding strength of the physiologically active
10 substance to the core and maintain the viscosity of the mixture so as not to reduce the workability.

 Where the coating layer comprises plural layers, the concentration of the physiologically active substance in each layer may be changed successively or gradually by selecting
15 for the content ratio or viscosity of the water-soluble polymer or by successive coating with mixtures varying in the ratio of the physiologically active substance and the other excipients. In the above case, it may be coated with a mixture in which the content ratio of the water-soluble polymer is out
20 of the range of about 0.1 to 50 weight %, as long as the coating layer as a whole contains about 0.1 to 50 weight % of the water-soluble polymer. Further, in forming the inactive coat according to known methods, the coating layer may comprise some layers such that the inactive layer may block each layer
25 containing the physiologically active substance.

 Also, in case of two or more physiologically active substances not suited in the compatibility, the core may be coated by employing each mixture together or separately.

 The above coated material is dried, and passed through
30 sieves to obtain a "composition" having uniform size. Because the form of the powder is usually according to the core, a fine granule being in the form of a rough sphere may be obtained.

 As the sieve may be employed, for example a #50 circular sieve (300 μ m). The composition is obtained by selecting those which
35 pass through the #50 circular sieve.

The "fine granule" in the present invention can be produced in accordance with in the same manner as above granulation method, for example, a method which comprises coating the composition with an enteric coating layer, in order to protect the acid-labile physiologically active substance or to impart enteric dissolution. If necessary, the composition coated with an enteric coating layer may be further coated by a water-soluble sugar alcohol, preferably mannitol. In such case, the strength of the orally disintegrable tablet comprising fine granules is improved.

The "enteric coating layer" is preferably a layer having about 20 to 70 μm , preferably about 30 to 50 μm of thickness and coating the whole surface of the composition containing the physiologically active substance. Accordingly, the smaller particle diameter of the composition, the higher the weight % of the enteric coating layer in the whole fine granule.

In the fine granule of the present invention, the "enteric coating layer" is about 30 to 70 weight %, preferably about 50 to 70 weight %, of the fine granule as a whole.

The "enteric coating layer" may be constructed by plural (e.g., 2 or 3) layers. For example, employed is a method which comprises coating a composition with an enteric coating layer having polyethyleneglycol, and then with an enteric coating layer having triethyl citrate, followed by being coated with an enteric coating layer having polyethyleneglycol.

The "orally disintegrable tablet" of the present invention can be produced in accordance with a conventional method in the pharmaceutical field. Such methods include, for instance, a method which comprises blending the "fine granules" and the "additives", and molding, if necessary followed by drying. Concretely mentioned is a method which comprises blending the fine granules and the additives, if necessary with water, and molding, if necessary followed by

drying.

The "blending procedure" can be carried out by any of the conventional blending techniques such as admixing, kneading, granulating, etc. The above "blending procedure" is carried out, for instance, by using an apparatus such as Vertical Granulator GV10 [manufactured by Powrex Corp. (Japan)], Universal Kneader [manufactured by Hata Iron Works Co., Ltd. (Japan)], fluidized bed granulator LAB-1 and FD-3S [manufactured by Powrex Corp. (Japan)], V-shape mixer, tumbling mixer, and so forth.

Preferred example of the method for the "orally disintegrable tablet" of the present invention is a method which comprises:

- (i) coating a core comprising crystalline cellulose and lactose with an acid-labile physiologically active substance and a basic inorganic salt, followed by being coated with a coating layer comprising a water-soluble polymer to obtain a composition,
- (ii) coating the resultant composition with an enteric coating layer having polyethyleneglycol, and then with an enteric coating layer having triethyl citrate, and then with an enteric coating layer having polyethyleneglycol, followed by being coated by mannitol to obtain fine granule, and
- (iii) blending the resultant fine granule with an additive, followed by molding.

Where the pharmaceutical preparation of the present invention, especially an orally disintegrable tablet, is one which comprises no lubricant inside the preparation or tablet, such preparation can be preferably produced in accordance with methods described in JP-A-56-14098, Japanese Patent No. 2681601, etc. Such preparation, especially an orally disintegrable tablet, has sufficient strength. The above lubricant includes, for example, magnesium stearate, sucrose fatty acid ester, polyethyleneglycol, talc, stearic acid, etc.

The pharmaceutical preparations such as solid preparation (e.g., tablets, granules, fine granules, capsules, effervescent, etc.) and liquid preparation such as suspending preparation, which comprises the "fine granules" of the present invention can be produced in accordance with a conventional method.

The solid pharmaceutical preparation containing the "fine granules" of the present invention and the "orally disintegrable tablet" of the invention can also be produced by the wet tableting method. As the above method, it is preferably employed the methods described in JP-A-5-271054 and so forth. They can also be produced by drying after humidification. As the above method, preferably employed are the methods described in JP-A-9-48726, JP-A-8-291051 and so forth. Namely, it is effective to humidify before tableting or after tableting and then to dry, in order to enhance the hardness.

The "molding procedure" can be carried out, for instance, by tableting with a pressure of 0.5 to 3 ton/cm², preferably 1 to 2 ton/cm² by using a single-punch tableting machine [Kikusui Seisakusho (Japan)] or a rotary type tableting machine [Kikusui Seisakusho (Japan)] when a solid preparation is a tablet, especially an orally disintegrable tablet.

The "drying procedure" can be carried out by any of the techniques used commonly in the art, such as vacuum drying, fluidized-bed drying, etc.

The "fine granules" of the invention can be used for a pharmaceutical preparation. The pharmaceutical preparation includes, for example, a solid preparation such as tablet, granule, fine granule, capsule, effervescent, etc.; a liquid preparation such as a suspension preparation, etc. Among others, a tablet is preferred. Such tablet preferably has suitable strength so as to be stable through production

processes and distributions.

A solid pharmaceutical preparation comprising the fine granule of the invention is used for an orally disintegrable tablet and can be administered without water or together with water.

As administration methods, there are listed (1) a method of administration by dissolution or disintegration together with a little water, or without water and with saliva in the oral cavity, not to be swallowed as it is, or (2) a method of administration with water, where it is swallowed as it is.

Also, the tablet may be administered dissolved or disintegrated with water.

The "orally disintegrable tablet" of the present invention is advantageously used in (a) cases where administration without water is necessary, (b) cases of administration to a patients who have difficulty in swallowing tablets, or (c) cases of administration to the aged or to children where there is a fear of blocking the throat if it is in usual tablet form.

In case of the above (a), the orally disintegrable tablet is preferably used for antipyretic agents, analgesic agents, anti-inflammatory agents, antianxiety drugs, antitussive-expectorants, anti motion sickness agents, drugs for prevention and treatment for car-sickness, and so forth.

In case of the above (b), the orally disintegrable tablet is preferably used for preventing and/or treating hypertension, hyperlipemia, diabetes, bronchial asthma, cerebrovascular diseases, and so forth.

The "orally disintegrable tablet" of the present invention and the pharmaceutical preparation which comprises the "fine granules" of the present invention can be safely administered orally to mammals such as mice, rats, rabbits, cats, dogs, bovines, horses, monkeys, humans, etc.

With the dosage of the "orally disintegrable tablet" of

the present invention and the pharmaceutical preparation which comprises the "fine granules" of the present invention, varies depending on the pharmaceutically active ingredient, subject, kinds of diseases, etc., the dosage can be selected so that the dosage of the pharmaceutically active ingredient is an effective amount.

For instance, when a benzimidazole compound (I) or a salt thereof such as lansoprazole is employed as an acid-labile physiologically active substance, especially a pharmaceutically active ingredient, the "orally disintegrable tablet" of the present invention and the pharmaceutical preparation which comprises the "fine granules" of the present invention is useful for treatment and prevention of digestive ulcer (e.g., gastric ulcer, duodenal ulcer, anastomotic ulcer, Zollinger-Ellison syndrome, etc), gastritis, reflux esophagitis, etc.; eradication of *H. pylori*; suppression of gastrointestinal bleeding caused by digestive ulcer, acute stress ulcer and hemorrhagic gastritis; suppression of gastrointestinal bleeding caused by invasive stress (e.g., stress caused by cerebrovascular disease, head injury, failure of many organs, burn injury of a wide range, which necessitate a large-scale operation necessitating the following intensive management, or intensive care); treatment and prevention of ulcer caused by non-steroidal anti-inflammatory agent; treatment and prevention of gastric hyperacidity and ulcer caused by postoperative stress; administration before anesthesia, etc. The dosage of the preparation per an adult (body weight: 60 kg) is about 0.5 to 1,500 mg/day, preferably about 5 to 150 mg/day, as a benzimidazole compound (I) or a salt thereof such as lansoprazole.

The "orally disintegrable tablet" of the present invention and the pharmaceutical preparation which comprises the "fine granules" of the present invention can be administered once a day, or two or three times separately a day.

BEST MODE FOR CARRYING OUT THE INVENTION

The following Examples and Reference Examples are further illustrative but by no means limitative of the present invention.

Unless otherwise specifically indicated, the following "%" means weight %.

Also, the content of the hydroxypropoxyl group is measured in accordance with the methods described in Japanese Pharmacopoeia (13th edition).

The physical properties of the tablets and granules prepared in Examples were determined by the following test methods.

(1) Hardness test

Determination was carried out with a tablet hardness tester [manufactured by Toyama Sangyo, Co. Ltd. (Japan)]. The test was performed in 10 runs and mean values were shown.

(2) Oral disintegration time

Time for complete disintegration only by saliva in the oral cavity was determined.

(3) Remaining ratio

According to the 2nd method of the dissolution test defined in Japanese Pharmacopoeia, the dissolution test was performed by using 500 ml of 0.1N HCl (75 rpm) for 1 hour. Then, the enteric fine granule was collected by means of the sieve.

The content of the drug in the collected fine granule was measured by the HPLC method. The remaining ratio was calculated according to the following expression with the content of the drug in the tablet which is measured separately by HPLC method.

Remaining ratio = (Content of the drug in the collected fine granule after the dissolution test using 0.1N HCl for 1 hour)/(Content of the drug in the tablet)

(4) Acid-resistance: Dissolution using 0.1N HCl

According to the 2nd method of the dissolution test defined in Japanese Pharmacopoeia, the dissolution test was performed by using 500 ml of 0.1N HCl (75 rpm) for 1 hour. Then, test medium was collected and filtered by using a 0.45 μ m membrane filter. The absorbance was measured to calculate the dissolution of the drug into 0.1N HCl.

(5) Average particle diameter: Volume based distribution median diameter (median diameter: 50% particle diameter from cumulative distribution)

Determination was carried out with Raser Diffraction Analyzer, type: HEROS RODOS [trade name, manufactured by Sympatec (Germany)].

Examples

Example 1

(1) Production of granules having a core

A centrifugal fluidized coating granulator [manufactured by Powrex Corp. (Japan), MP-10 (Type 2)] is charged with 300 g of Nonpareil 105 (70-140) (particle diameter of 100 to 200 μ m). With the inlet air temperature and the temperature of the loading being controlled at 85 °C and about 28 °C respectively, the Nonpareil is coated by spraying a bulk liquid of the following composition prepared in advance in accordance with the tangential spray method at a spray rate of 20 g /min. The spraying operation is stopped when the specified amount of the bulk liquid has been sprayed, and then drying is carried out in the granulator for 7 minutes. The resulting granules are sieved through a #60 circular sieve (250 μ m) and a #100 circular sieve (150 μ m) to provide 750 g of granules having a core.

Bulk liquid:

Lansoprazole	300 g
Magnesium carbonate	100 g
L-HPC	50 g

37

HPC (Type SSL)	100 g
Water	1650 g

- (2) Production of film-undercoated granules having a core
A centrifugal fluidized coating granulator [manufactured
by Powrex Corp. (Japan), MP-10 (Type 2)] is charged with 680
5 g of the above granules having a core. With the inlet air
temperature and the temperature of the loading being
controlled at 70 °C and about 36 °C, respectively, an
undercoating liquid of the following composition prepared in
advance is sprayed in accordance with the tangential spray
10 method at a spray rate of 10 g /min. to provide 650 g of
film-undercoated granules having a core.

Undercoating liquid:

HPMC	32 g
(Type 2910, viscosity: 3 centistokes)	
Talc	8 g
Water	760 g

- 15 (3) Production of enteric coated granules having a core
A centrifugal fluidized coating granulator [manufactured
by Powrex Corp. (Japan), MP-10 (Type 2)] is charged with 450
g of the above film-undercoated granules having a core. With
the inlet air temperature and the temperature of the loading
20 being controlled at 65 °C and about 36 °C, respectively, an
enteric film coating liquid of the following composition
prepared in advance is sprayed in accordance with the
tangential spray method at a spray rate of 17 g /min. The coated
powders are dried in vacuum at 40 °C for 16 hours, and sieved
25 through a #42 circular sieve (355 µm) and a #80 circular sieve
(177 µm) to provide 950 g of enteric coated granules having
a core.

Enteric film coating liquid:

38

Eudragit L30D-55	1078.3 g
Eudragit NE30D	138.5 g
Triethyl citrate	46.0 g
Glyceryl monostearate	23.1 g
Talc	16.0 g
Polysorbate 80	9.0 g
Yellow iron oxide	0.5 g
Water	2038.5 g

Sieve	weight ratio
#18 (850 μ m) on	0 %
#30 (500 μ m) on	0 %
#200 (75 μ m) on	100 %
#200 (75 μ m) pass	0 %

(4) Production of granulated powders

A fluidized bed granulator [manufactured by Powrex Corp. (Japan), LAB-1] is charged with 1321.2 g of erythritol [manufactured by Nikken Chemical Co., Ltd. (Japan)], 360.0 g of low-substituted hydroxypropyl cellulose LH-32 [hydroxypropoxyl group contents of 8.8 %, manufactured by Shin-Etsu Chemical Co., Ltd. (Japan)], 18.0 g of citric acid anhydrous, and 1.8 g of aspartame, and granulation is carried out while spraying a solution which is prepared by dissolving 3.6 g of polyethylene glycol (PEG-6000) in 896.4 ml of purified water. The granules are dried to provide granulated powders. To the granulated powders are added 90.0 g of crospovidone and 5.4 g of magnesium stearate, which is admixed in a bag to give mixed powders.

(5) Production of orally disintegrable tablets

Hereinafter, the above "enteric coated granules having a core" is referred to as "enteric coated powders".

200.0 g of the above enteric coated powders and 300.0 g of the above mixed powders are tabletted using Autograph (trade

name; compressing force measurement apparatus) with a punch having a beveled edge, 11 mm in diameter, at a tableting pressure of 1.0 ton/cm² to provide tablets each weighing 500 mg.

5

Reference Example 1

An alkaline cellulose comprising 24.1 % of NaOH, 1.7 % of Na₂CO₃, 42.9 % of cellulose, 31.8 % of H₂O was obtained by immersing a wood pulp in 49% aqueous solution of sodium hydroxide and then by pressing it. A reactor was charged with 100 weight parts of the alkaline cellulose. Then, nitrogen gas replacement was carried out. After the replacement, 5 weight parts of propylene oxide was charged in the reactor and reacted with stirring at 40 °C for 1 hour, at 50 °C for 1 hour and at 70 °C for 1 hour to obtain 103 weight parts of a reactant.

15

On the other side, a kneader was charged with 2.5 weight parts of hot water at 65 °C and 0.13 weight parts of glacial acetic acid (about 40 weight % against equivalent for neutralization, initial neutralized acid) and therein, 1 weight part of the above resulting alkaline cellulose was dispersed. Then, the temperature was set at 30 °C to dissolve a part of the reactant, and 0.20 weight part of glacial acetic acid (the remainder of an equivalent for neutralization, complete neutralized acid) to obtain a processed fiber product containing a part of dissolution and a part of deposit.

20

The resulting product was washed with hot water at about 80 °C, drained, dried, ground by means of a high rolling impact grinder, and sifted by means of a 100 mesh sieve to obtain the powder of low-substituted hydroxypropyl cellulose LH-33 (the content of hydroxypropoxyl group: 5.8 weight %, the average particle diameter: 17.8 μm).

25

30

Reference Example 2

Powders of low-substituted hydroxypropyl cellulose LH-23

(hydroxypropoxyl group contents: 5.7 weight %, average particle diameter: 30.8 μm) were obtained in the same manner as in Reference Example 1.

5 Example 2

(1) Production of granules having a core

A centrifugal fluidized coating granulator [manufactured by Powrex Corp. (Japan), MP-10 (Type 2)] was charged with 300 g of Nonpareil 105 [(trade name) particle diameter: 100 to 200 μm]. With the inlet air temperature and the temperature of the loading being controlled at 70 °C and about 30 °C, respectively, the Nonpareil was coated by spraying a spray liquid of the following composition prepared in advance in accordance with the tangential spray method at a spray rate of 22 g/min., and then drying was carried out in the granulator for 10 minutes. The resulting granules were sieved through a #48 circular sieve (300 μm) and a #100 circular sieve (150 μm) to provide 2186 g of powders (150 to 300 μm) having a core.

20 Spray liquid:

Lansoprazole	927 g
Magnesium carbonate	309 g
Low-substituted hydroxypropyl cellulose LH-32	154.5 g
(hydroxypropoxyl group contents: 8.8 wt %)	
(average particle diameter: 17.57 μm)	
Hydroxypropyl cellulose (Type SSL)	309 g
Purified water	3955 g

(2) Production of film-undercoated granules having a core

A centrifugal fluidized coating granulator [manufactured by Powrex Corp. (Japan), MP-10 (Type 2)] was charged with 2040 g of the above granules having a core. With the inlet air temperature and the temperature of the loading being controlled at 75 °C and about 40 °C, respectively, an undercoating liquid of the following composition prepared in

advance was sprayed in accordance with the tangential spray method at a spray rate of 13 g /min. to provide 2145 g of film-undercoated granules having a core.

5 Undercoating liquid:

Hydroxypropylmethylcellulose	264 g
(Type 2910, viscosity: 3 centistokes)	
Purified water	5016 g

(3) Production of enteric coated granules having a core

A centrifugal fluidized coating granulator [manufactured by Powrex Corp. (Japan), MP-10 (Type 2)] was charged with 1710 g of the above film-undercoated granules having a core. With the inlet air temperature and the temperature of the loading being controlled at 70 °C and about 40 °C, respectively, an enteric film coating liquid of the following composition prepared in advance was sprayed in accordance with the tangential spray method at a spray rate of 17 g /min., and dried for 7 minutes, and then sieved through a #42 circular sieve (355 µm) and a #80 circular sieve (177 µm) to provide 2393 g of enteric coated powders (177 to 355 µm) having a core.

20 Enteric film coating liquid:

Eudragit L30D-55	5016.4 g
Eudragit NE30D	559.0 g
Triethyl citrate	333.7 g
Glyceryl monostearate	106.5 g
Polysorbate 80	34.8 g
Red iron oxide	1.8 g
Purified water	2547.1 g

(4) Production of enteric coated and mannitol coated granules having a core

A centrifugal fluidized coating granulator [manufactured by Powrex Corp. (Japan), MP-10 (Type 2)] was charged with 600

g of the above enteric coated granules having a core. With the inlet air temperature and the temperature of the loading being controlled at 65 °C and about 32 °C, respectively, an film coating liquid of the following composition prepared in advance was sprayed in accordance with the tangential spray method at a spray rate of 11 g/min., and then dried for 7 minutes to provide 617 g of enteric coated and mannitol coated granules having a core.

The average particle diameter of the obtained granules was 334.1 µm.

Film coating liquid:

Mannitol	33 g
Purified water	297 g

(5) Production of mannitol-granulated powders

A fluidized bed granulator [manufactured by Powrex Corp. (Japan), LAB-1] was charged with 800 g of mannitol [manufactured by Merck Japan Co., Ltd.], and granulation was carried out while spraying 315 g of purified water. The granules were dried to provide 727.3 g of granulated powders.

(6) Production of mixed powders

To 97.3 g of the above mannitol-granulated powders were added 105 g of the above enteric coated and mannitol coated granules having a core, 15.0 g of low-substituted hydroxypropyl cellulose LH-33 (hydroxypropoxyl group contents: 5.8 weight %, average particle diameter: 17.8 µm), 22.5 g of crystalline cellulose [CEOLUS KG-801 (trade name), manufactured by Asahi Chemical Co., Ltd. (Japan)], 7.5 g of crospovidone, 1.5 g of citric acid anhydrous, 0.45 g of aspartame and 0.75 g of magnesium stearate, which was admixed in a bag to give mixed powders.

(7) Production of orally disintegrable tablets

250.0 g of the above mixed powders were tabletted using Autograph (trade name; compressing force measurement apparatus) with a punch (15R), 11 mm in diameter, at a tableting pressure of 1.5 ton/cm², to provide tablets each weighing 500 mg.

The hardness and oral disintegration time of each tablet thus obtained were 5.9 kg and 30 seconds, respectively.

Example 3

(1) Production of granules having a core

A centrifugal fluidized coating granulator [manufactured by Powrex Corp. (Japan), MP-10 (Type 2)] was charged with 900 g of Nonpareil 105 (trade name) (particle diameter of 100 to 200 µm). With the inlet air temperature and the temperature of the loading being controlled at 75 °C and about 29 °C respectively, the Nonpareil was coated by spraying a bulk liquid of the following composition prepared in advance in accordance with the tangential spray method at a spray rate of 22 g /min. The spraying operation was stopped when the specified amount 5654.7 g of the bulk liquid had been sprayed, and then drying was carried out in the granulator for 10 minutes. The resulting granules were sieved through a #60 circular sieve (250 µm) and a #100 circular sieve (150 µm) to provide 2424 g of granules having a core.

Bulk liquid:

Lansoprazole	1080 g
Magnesium carbonate	360 g
Low-substituted hydroxypropyl cellulose LH-32	180 g
(hydroxypropoxyl group contents: 8.8 weight %)	
Hydroxypropyl cellulose (Type SSL)	360 g
Purified water	4608 g

(2) Production of film-undercoated granules having a core

A centrifugal fluidized coating granulator [manufactured by Powrex Corp. (Japan), MP-10 (Type 2)] was charged with 2337.5 g of the above granules having a core. With the inlet air temperature and the temperature of the loading being controlled at 80 °C and about 41 °C, respectively, an undercoating liquid of the following composition prepared in advance was sprayed in accordance with the tangential spray method at a spray rate of 18 g /min. The spraying operation was stopped when the specified amount 6050 g of the undercoating liquid had been sprayed, and then drying was carried out in the granulator for 10 minutes to provide 2551 g of film-undercoated granules having a core.

Undercoating liquid:

Hydroxypropyl methylcellulose	332.5 g
(Type 2910, viscosity: 3 centistokes)	
Low-substituted hydroxypropyl cellulose LH-32	17.5 g
(hydroxypropoxyl group contents: 8.8 weight %)	
(average particle diameter: 17.57 µm)	
Purified water	6650 g

(3) Production of enteric coated granules having a core

A centrifugal fluidized coating granulator [manufactured by Powrex Corp. (Japan), MP-10 (Type 2)] was charged with 570 g of the above film-undercoated granules having a core. With the inlet air temperature and the temperature of the loading being controlled at 75 °C and about 40 °C, respectively, an enteric film coating liquid of the following composition prepared in advance was sprayed in accordance with the tangential spray method at a spray rate of 18 g /min. The spraying operation was stopped when the specified amount 2646 g of the enteric film coating liquid had been sprayed, and then drying was carried out in the granulator for 8 minutes. The coated powders were sieved through a #42 circular sieve (355 µm) and a #70 circular sieve (212 µm) to provide 1116 g of

enteric coated granules having a core.

The average particle diameter of the obtained granules was 326.9 μm .

5 Enteric film coating liquid:

Eudragit L30D-55	1911 g
Eudragit NE30D	212.9 g
Triethyl citrate	127.1 g
Glyceryl monostearate	40.6 g
Polysorbate 80	13.3 g
Red iron oxide	0.8 g
Purified water	970.3 g

(4) Production of mixed powders

To 200 g of the above enteric coated granules having a core were added 189.7 g of mannitol, 30.0 g of low-substituted hydroxypropyl cellulose LH-23 (hydroxypropoxyl group contents: 5.8 weight %, average particle diameter: 17.8 μm), 60.0 g of crystalline cellulose [CEOLUS KG-801 (trade name), manufactured by Asahi Chemical Co., Ltd. (Japan)], 15.0 g of crospovidone, 2.8 g of citric acid anhydrous and 25 g of magnesium stearate, which was admixed in a bag to give mixed powders.

(5) Production of orally disintegrable tablets

250.0 g of the above mixed powders were tabletted using Autograph (trade name; compressing force measurement apparatus) with a punch (15R), 11 mm in diameter, at a tableting pressure of 1.5 ton/cm^2 , to provide tablets each weighing 500 mg.

The hardness and oral disintegration time of each tablet thus obtained were 4.2 kg and 24 seconds, respectively.

Example 4

(1) Production of granules having a core

A centrifugal fluidized coating granulator [manufactured by Powrex Corp. (Japan), MP-10 (Type 2)] was charged with 900 g of Nonpareil 105 (trade name) (particle diameter of 100 to 200 μm).

With the inlet air temperature and the temperature of the loading being controlled at 75 °C and about 32 °C respectively, the Nonpareil was coated by spraying a bulk liquid of the following composition prepared in advance in accordance with the tangential spray method at a spray rate of 20 g /min. The spraying operation was stopped when the specified amount 5654.7 g of the bulk liquid had been sprayed, and then drying was carried out in the granulator for 10 minutes. The resulting granules were sieved through a #48 circular sieve (300 μm) and a #100 circular sieve (150 μm) to provide 2280 g of granules having a core.

Bulk liquid:

Lansoprazole	1080 g
Magnesium carbonate	360 g
Low-substituted hydroxypropyl cellulose LH-32 (hydroxypropoxyl group contents: 8.8 weight %)	180 g
Hydroxypropyl cellulose (Type SSL)	360 g
Purified water	4608 g

20 (2) Production of film-undercoated granules having a core

A centrifugal fluidized coating granulator [manufactured by Powrex Corp. (Japan), MP-10 (Type 2)] was charged with 1020 g of the above granules having a core. With the inlet air temperature and the temperature of the loading being controlled at 85 °C and about 40 °C, respectively, an undercoating liquid of the following composition prepared in advance was sprayed in accordance with the tangential spray method at a spray rate of 15 g /min. The spraying operation was stopped when the specified amount 1980 g of the undercoating

liquid had been sprayed, and then drying was carried out in the granulator for 10 minutes to provide 1330.5 g of film-undercoated granules having a core.

5 Undercoating liquid:

Hydroxypropylmethylcellulose	120 g
(Type 2910, viscosity: 3 centistokes)	
Titanium oxide (TiO ₂)	240 g
Sterilized Talc (trade name)	240 g
[produced by Matsumura Sangyo Co. Ltd. (Japan)]	
Magnesium carbonate	120 g
Purified water	2880 g

- (3) Production of enteric coated granules having a core
- A centrifugal fluidized coating granulator [manufactured by Powrex Corp. (Japan), MP-10 (Type 2)] was charged with 460 g of the above film-undercoated granules having a core. With the inlet air temperature and the temperature of the loading being controlled at 80 °C and about 41 °C, respectively, an enteric film coating liquid of the following composition prepared in advance was sprayed in accordance with the tangential spray method at a spray rate of 13 g /min. The spraying operation was stopped when the specified amount 2205 g of the enteric film coating liquid had been sprayed.

Enteric film coating liquid:

Eudragit L30D-55	2290 g
Eudragit NE30D	253 g
Triethyl citrate	153 g
Glyceryl monostearate	20 g
Polysorbate 80	8 g
Titanium oxide (TiO ₂)	53 g
Sterilized Talc H (trade name)	53 g
[produced by Matsumura Sangyo Co. Ltd. (Japan)]	
Purified water	2420 g

(4) Production of enteric coated and mannitol coated granules having a core

5 Following (3), with the inlet air temperature and the
temperature of the loading being controlled at 80 °C and about
35 °C, respectively, an film coating liquid of the following
composition prepared in advance was sprayed in accordance with
the tangential spray method at a spray rate of 16 g /min. using
a centrifugal fluidized coating granulator [manufactured by
10 Powrex Corp. (Japan), MP-10 (Type 2)]. The spraying operation
was stopped when the specified amount 824 g of the film coating
liquid had been sprayed, and then drying was carried out in
the granulator for 10 minutes. The resulting granules were
sieved through a #42 circular sieve (355 µm) and a #60 circular
15 sieve (250 µm) to provide 806 g of enteric coated and mannitol
coated granules having a core.

The average particle diameter of the obtained granules
was 326.6 µm.

20 Film coating liquid:

Mannitol	320 g
Purified water	2880 g

(5) Production of mixed powders

To 120 g of the above enteric coated and mannitol coated
granules having a core were added 87.75 g of mannitol, 8.5
25 g of low-substituted hydroxypropyl cellulose LH-23
(hydroxypropoxyl group contents: 5.8 weight %), 4.5 g of
low-substituted hydroxypropyl cellulose LH-33
(hydroxypropoxyl group contents: 5.8 weight %), 19.5 g of
crystalline cellulose [CEOLUS KG-801 (trade name),
30 manufactured by Asahi Chemical Co., Ltd. (Japan)], 6.5 g of
crospovidone, 1.3 g of citric acid anhydrous, 1.3 g of aspartame
and 0.65 g of magnesium stearate, which was admixed in a bag
to give mixed powders.

(6) Production of orally disintegrable tablets

250.0 g of the above mixed powders were tabletted using Autograph (trade name; compressing force measurement apparatus) with a punch (15R), 11 mm in diameter, at a
5 tableting pressure of 1.5 ton/cm², to provide tablets each weighing 500 mg.

The hardness and oral disintegration time of each tablet thus obtained were 3.9 kg and 20.5 seconds, respectively.

10 The remaining ratio of the obtained tablet after acid-resistance test was 97%.

Example 5

(1) Production of granules having a core

15 A centrifugal fluidized coating granulator [manufactured by Powrex Corp. (Japan), MP-10 (Type 2)] was charged with 900 g of Nonpareil 105 (trade name) (particle diameter of 100 to 200 µm). With the inlet air temperature and the temperature of the loading being controlled at 65 °C and about 30 °C
20 respectively, the Nonpareil was coated by spraying a bulk liquid of the following composition prepared in advance in accordance with the tangential spray method at a spray rate of 22 g /min. The spraying operation was stopped when the specified amount 5661 g of the bulk liquid had been sprayed,
25 and then drying was carried out in the granulator for 8 minutes.

The resulting granules were sieved through a #42 circular sieve (350 µm) and a #100 circular sieve (150 µm) to provide 2074 g of granules having a core.

30 Bulk liquid:

Lansoprazole	1080 g
Magnesium carbonate	360 g
Low-substituted hydroxypropyl cellulose LH-32	180 g
(hydroxypropoxyl group contents: 8.8 weight %)	

Hydroxypropyl cellulose (Type SSL)	360 g
Purified water	4680 g

- (2) Production of film-undercoated granules having a core
- A centrifugal fluidized coating granulator [manufactured by Powrex Corp. (Japan), MP-10 (Type 2)] was charged with 2074 g of the above granules having a core. With the inlet air temperature and the temperature of the loading being controlled at 78 °C and about 40 °C, respectively, an undercoating liquid of the following composition prepared in advance was sprayed in accordance with the tangential spray method at a spray rate of 22 g /min. The spraying operation was stopped when the specified amount 1980 g of the undercoating liquid had been sprayed, and then drying was carried out in the granulator for 9 minutes. The resulting granules were sieved through a #42 circular sieve (350 µm) and a #100 circular sieve (150 µm) to provide 2555 g of film-undercoated granules having a core.

Undercoating liquid:

Hydroxypropylmethylcellulose (Type 2910, viscosity: 3 centistokes)	252 g
Titanium oxide (TiO ₂)	108 g
Sterilized Talc (trade name) [produced by Matsumura Sangyo Co. Ltd. (Japan)]	108 g
Low-substituted hydroxypropyl cellulose LH-32 (hydroxypropoxyl group contents: 8.8 weight %)	180 g
Mannitol	252 g
Purified water	3600 g

- (3) Production of enteric coated granules having a core
- A centrifugal fluidized coating granulator [manufactured by Powrex Corp. (Japan), MP-10 (Type 2)] was charged with 1320 g of the above film-undercoated granules having a core. With the inlet air temperature and the temperature of the loading

being controlled at 80 °C and about 42 °C, respectively, an enteric film coating liquid (A) of the following composition prepared in advance was sprayed in accordance with the tangential spray method at a spray rate of 22 g /min. The specified amount 1638 g of the enteric film coating liquid had been sprayed.

Enteric film coating liquid (A):

Eudragit L30D-55	1219.2 g
Eudragit NE30D	134.4 g
Polyethylene glycol 6000	40.8 g
Glyceryl monostearate	24.0 g
Polysorbate 80	7.2 g
Ferric oxide	0.24 g
Ferric oxide (yellow)	0.24 g
Citric acid anhydrous	0.48 g
Purified water	1693 g

Following this, with the inlet air temperature and the temperature of the loading being controlled at 76 °C and about 42 °C, respectively, an enteric film coating liquid (B) of the following composition prepared in advance was sprayed in accordance with the tangential spray method at a spray rate of 22 g /min. The specified amount 6552 g of the enteric film coating liquid had been sprayed.

Enteric film coating liquid (B):

Eudragit L30D-55	4032 g
Eudragit NE30D	447.8 g
Triethyl citrate	269.3 g
Glyceryl monostearate	86.4 g
Polysorbate 80	25.9 g
Ferric oxide	0.86 g
Ferric oxide (yellow)	0.86 g

Citric acid anhydrous	0.72 g
Purified water	2624 g

Following this, with the inlet air temperature and the temperature of the loading being controlled at 80 °C and about 42 °C, respectively, an enteric film coating liquid (A) of the above mentioned composition prepared in advance was sprayed in accordance with the tangential spray method at a spray rate of 22 g /min. The specified amount 819 g of the enteric film coating liquid had been sprayed.

(4) Production of enteric coated and mannitol coated granules having a core

Following (3), with the inlet air temperature and the temperature of the loading being controlled at 85 °C and about 35 °C, respectively, an film coating liquid of the following composition prepared in advance was sprayed in accordance with the tangential spray method at a spray rate of 22 g /min. using a centrifugal fluidized coating granulator [manufactured by Powrex Corp. (Japan), MP-10 (Type 2)]. The spraying operation was stopped when the specified amount 882 g of the film coating liquid had been sprayed, and then drying was carried out in the granulator for 10 minutes. The resulting granules were sieved through a #35 circular sieve (420 µm) and a #60 circular sieve (250 µm) to provide 1964 g of enteric coated and mannitol coated granules having a core.

The average particle diameter of the obtained granules was 333.7 µm.

Film coating liquid:

Mannitol	180 g
Purified water	1080 g

(5) Production of mixed powders

To 270 g of the above enteric coated and mannitol coated

granules having a core were added 204.0 g of mannitol, 30 g of low-substituted hydroxypropyl cellulose LH-33 (hydroxypropoxyl group contents: 5.8 weight %), 30 g of crystalline cellulose [CEOLUS KG-801 (trade name), manufactured by Asahi Chemical Co., Ltd. (Japan)], 15 g of crospovidone, 3 g of citric acid anhydrous, 9 g of aspartame, 6 g of magnesium stearate and 3 g of flavor [STRAWBERRY DURAROME (trade name), manufactured by Nihon Filmeneich Co., Ltd. (Japan)], which was admixed in a bag to give mixed powders.

(6) Production of orally disintegrable tablets

570 g of the above mixed powders were tabletted using Autograph (trade name; compressing force measurement apparatus) with a punch having a beveled edge, 13 mm in diameter, at a tableting pressure of 1.5 ton/cm², to provide tablets each weighing 570 mg.

The hardness and oral disintegration time of each tablet thus obtained were 2.6 kg and 20 seconds, respectively.

The acid-resistance of the obtained tablet was 3.5 %.

Example 6

(1) Production of granules having a core

A centrifugal fluidized coating granulator [manufactured by Powrex Corp. (Japan), MP-10 (Type 2)] was charged with 750 g of Nonpareil 105 (trade name) (particle diameter of 100 to 200 µm). With the inlet air temperature and the temperature of the loading being controlled at 65 °C and about 30 °C respectively, the Nonpareil was coated by spraying a bulk liquid of the following composition prepared in advance in accordance with the tangential spray method at a spray rate of 22 g /min. The spraying operation was stopped when the specified amount 4717.5 g of the bulk liquid had been sprayed, and then drying was carried out in the granulator for 8 minutes.

The resulting granules were sieved through a #42 circular sieve (350 µm) and a #100 circular sieve (150 µm) to provide

1811 g of granules having a core.

Bulk liquid:

Lansoprazole	900 g
Magnesium carbonate	300 g
Low-substituted hydroxypropyl cellulose LH-32 (hydroxypropoxyl group contents: 8.8 weight %)	150 g
Hydroxypropyl cellulose (Type SSL)	300 g
Purified water	3900 g

- 5 (2) Production of film-undercoated granules having a core
A centrifugal fluidized coating granulator [manufactured
by Powrex Corp. (Japan), MP-10 (Type 2)] was charged with 1811
g of the above granules having a core. With the inlet air
temperature and the temperature of the loading being
10 controlled at 78 °C and about 38 °C, respectively, an
undercoating liquid of the following composition prepared in
advance was sprayed in accordance with the tangential spray
method at a spray rate of 22 g /min. The spraying operation
was stopped when the specified amount 5274 g of the undercoating
15 liquid had been sprayed, and then drying was carried out in
the granulator for 9 minutes. The resulting granules were
sieved through a #42 circular sieve (350 µm) and a #100 circular
sieve (150 µm) to provide 2628 g of film-undercoated granules
having a core.

20

Undercoating liquid:

Hydroxypropylmethylcellulose (Type 2910, viscosity: 3 centistokes)	378 g
Titanium oxide (TiO ₂)	162 g
Sterilized Talc (trade name) [produced by Matsumura Sangyo Co. Ltd. (Japan)]	162 g
Low-substituted hydroxypropyl cellulose LH-32 (hydroxypropoxyl group contents: 8.8 weight %)	270 g
Mannitol	378 g

Purified water

5400 g

(3) Production of enteric coated granules having a core
A centrifugal fluidized coating granulator [manufactured
by Powrex Corp. (Japan), MP-10 (Type 2)] was charged with 1560
5 g of the above film-undercoated granules having a core. With
the inlet air temperature and the temperature of the loading
being controlled at 70 °C and about 40 °C, respectively, an
enteric film coating liquid (A) of the following composition
prepared in advance was sprayed in accordance with the
10 tangential spray method at a spray rate of 19 g /min. The
specified amount 6048 g of the enteric film coating liquid had
been sprayed.

Enteric film coating liquid (A):

Eudragit L30D-55	4032 g
Eudragit NE30D	447.8 g
Triethyl citrate	269.3 g
Glyceryl monostearate	86.4 g
Polysorbate 80	25.9 g
Ferric oxide	0.86 g
Ferric oxide (yellow)	0.86 g
Citric acid anhydrous	0.72 g
Purified water	2624 g

15

Following this, with the inlet air temperature and the
temperature of the loading being controlled at 72 °C and about
42 °C, respectively, an enteric film coating liquid (B) of the
following composition prepared in advance was sprayed in
20 accordance with the tangential spray method at a spray rate
of 19 g /min. The specified amount 819 g of the enteric film
coating liquid had been sprayed.

Enteric film coating liquid (B):

Eudragit L30D-55	609.6 g
------------------	---------

Eudragit NE30D	68.0 g
Polyethylene glycol 6000	20.4 g
Glyceryl monostearate	12.0 g
Polysorbate 80	3.6 g
Ferric oxide	0.12 g
Ferric oxide (yellow)	0.12 g
Citric acid anhydrous	0.24 g
Purified water	846.7 g

(4) Production of enteric coated and mannitol coated granules having a core

5 Following (3), while the inlet air temperature and the temperature of the loading being controlled at 65 °C and about 38 °C, respectively, an film coating liquid of the following composition prepared in advance was sprayed in accordance with the tangential spray method at a spray rate of 19 g /min. using a centrifugal fluidized coating granulator [manufactured by 10 Powrex Corp. (Japan), MP-10 (Type 2)]. The spraying operation was stopped when the specified amount 882 g of the film coating liquid had been sprayed, and then drying was carried out in the granulator for 17 minutes. The resulting granules were 15 sieved through a #35 circular sieve (420 µm) and a #60 circular sieve (250 µm) to provide 2825 g of enteric coated and mannitol coated granules having a core.

 The average particle diameter of the obtained granules was 330.5 µm.

20 Film coating liquid:

Mannitol	180 g
Purified water	1080 g

(5) Production of mixed powders

 To 270 g of the above enteric coated and mannitol coated granules having a core were added 204.0 g of mannitol, 30 g 25 of low-substituted hydroxypropyl cellulose LH-33

(hydroxypropoxyl group contents: 5.8 weight %), 30 g of crystalline cellulose [CEOLUS KG-801 (trade name), manufactured by Asahi Chemical Co., Ltd. (Japan)], 15 g of crospovidone, 3 g of citric acid anhydrous, 9 g of aspartame, 6 g of magnesium stearate and 3 g of flavor [STRAWBERRY DURAROME (trade name), manufactured by Nihon Filmenich Co., Ltd. (Japan)], which was admixed in a bag to give mixed powders.

(6) Production of orally disintegrable tablets

570 g of the above mixed powders were tabletted using Autograph (trade name; compressing force measurement apparatus) with a punch having a beveled edge, 13 mm in diameter, at a tableting pressure of 1.5 ton/cm², to provide tablets each weighing 570 mg.

The hardness and oral disintegration time of each tablet thus obtained were 3.1 kg and 22 seconds, respectively.

The acid-resistance of the obtained tablet was 2.5 %.

Example 7

(1) Production of granules having a core

A centrifugal fluidized coating granulator [manufactured by Powrex Corp. (Japan), MP-10 (Type 2)] was charged with 750 g of Nonpareil 105 (trade name) (particle diameter of 100 to 200 μm). With the inlet air temperature and the temperature of the loading being controlled at 75 °C and about 30 °C respectively, the Nonpareil was coated by spraying a bulk liquid of the following composition prepared in advance in accordance with the tangential spray method at a spray rate of 20 g /min. The spraying operation was stopped when the specified amount 4717.5 g of the bulk liquid had been sprayed, and then drying was carried out in the granulator for 10 minutes to provide 1842 g of granules having a core.

Bulk liquid:

Lansoprazole

900 g

Magnesium carbonate	300 g
Low-substituted hydroxypropyl cellulose LH-32 (hydroxypropoxyl group contents: 8.8 weight %)	150 g
Hydroxypropyl cellulose (Type SSL)	300 g
Purified water	3900 g

(2) Production of film-undercoated granules having a core

A centrifugal fluidized coating granulator [manufactured by Powrex Corp. (Japan), MP-10 (Type 2)] was charged with 1842 g of the above granules having a core. With the inlet air temperature and the temperature of the loading being controlled at 74 °C and about 38 °C, respectively, an undercoating liquid of the following composition prepared in advance was sprayed in accordance with the tangential spray method at a spray rate of 19 g /min. The spraying operation was stopped when the specified amount 5365 g of the undercoating liquid had been sprayed, and then drying was carried out in the granulator for 9 minutes. The resulting granules were sieved through a #42 circular sieve (350 µm) and a #100 circular sieve (150 µm) to provide 2770 g of film-undercoated granules having a core.

Undercoating liquid:

Hydroxypropylmethylcellulose (Type 2910, viscosity: 3 centistokes)	378 g
Titanium oxide (TiO ₂)	162 g
Sterilized Talc (trade name) [produced by Matsumura Sangyo Co. Ltd. (Japan)]	162 g
Low-substituted hydroxypropyl cellulose LH-32 (hydroxypropoxyl group contents: 8.8 weight %)	270 g
Mannitol	378 g
Purified water	5400 g

(3) Production of enteric coated granules having a core
A centrifugal fluidized coating granulator [manufactured

by Powrex Corp. (Japan), MP-10 (Type 2)] was charged with 1300 g of the above film-undercoated granules having a core. With the inlet air temperature and the temperature of the loading being controlled at 78 °C and about 39 °C, respectively, an enteric film coating liquid (A) of the following composition prepared in advance was sprayed in accordance with the tangential spray method at a spray rate of 21 g /min. The spraying operation was stopped when the specified amount 5040 g of the enteric film coating liquid had been sprayed, and then drying was carried out in the granulator for 16 minutes. The resulting granules were sieved through a #35 circular sieve (420 µm) and a #60 circular sieve (250 µm) to provide 2453 g of enteric coated granules having a core.

15 Enteric film coating liquid (A):

Eudragit L30D-55	4032 g
Eudragit NE30D	447.8 g
Triethyl citrate	269.3 g
Glyceryl monostearate	86.4 g
Polysorbate 80	25.9 g
Ferric oxide	0.86 g
Ferric oxide (yellow)	0.86 g
Citric acid anhydrous	0.72 g
Purified water	2624 g

A centrifugal fluidized coating granulator [manufactured by Powrex Corp. (Japan), MP-10 (Type 2)] was charged with 1000 g of the above enteric coated granules having a core. With the inlet air temperature and the temperature of the loading being controlled at 80 °C and about 38 °C, respectively, an enteric film coating liquid (B) of the following composition prepared in advance was sprayed in accordance with the tangential spray method at a spray rate of 19 g /min. The specified amount 273 g of the enteric film coating liquid had been sprayed.

Enteric film coating liquid (B):

Eudragit L30D-55	610.4 g
Eudragit NE30D	68.0 g
Polyethylene glycol 6000	20.4 g
Glyceryl monostearate	12.0 g
Polysorbate 80	3.6 g
Ferric oxide	0.12 g
Ferric oxide (yellow)	0.12 g
Citric acid anhydrous	0.24 g
Purified water	845.12 g

- 5 (4) Production of enteric coated and mannitol coated granules having a core

Following (3), while the inlet air temperature and the temperature of the loading being controlled at 75 °C and about 35 °C, respectively, an film coating liquid of the following composition prepared in advance was sprayed in accordance with the tangential spray method at a spray rate of 20 g /min. using a centrifugal fluidized coating granulator [manufactured by Powrex Corp. (Japan), MP-10 (Type 2)]. The spraying operation was stopped when the specified amount 294 g of the film coating liquid had been sprayed, and then drying was carried out in the granulator for 10 minutes. The resulting granules were sieved through a #35 circular sieve (420 µm) and a #60 circular sieve (250 µm) to provide 1061 g of enteric coated and mannitol coated granules having a core.

20 The average particle diameter of the obtained granules was 307.1 µm.

Film coating liquid:

Mannitol	120 g
Purified water	720 g

- (5) Production of mixed powders

To 270 g of the above enteric coated and mannitol coated granules having a core were added 207 g of mannitol, 30 g of low-substituted hydroxypropyl cellulose LH-33 (hydroxypropoxyl group contents: 5.8 weight %), 30 g of crystalline cellulose [CEOLUS KG-801 (trade name), manufactured by Asahi Chemical Co., Ltd. (Japan)], 15 g of crospovidone, 3 g of citric acid anhydrous, 9 g of aspartame, 6 g of magnesium stearate and 3 g of flavor [STRAWBERRY DURAROME (trade name), manufactured by Nihon Filmenich Co., Ltd. (Japan)], which was admixed in a bag to give mixed powders.

(6) Production of orally disintegrable tablets

570 g of the above mixed powders were tabletted using Autograph (trade name; compressing force measurement apparatus) with a punch having a beveled edge, 13 mm in diameter, at a tableting pressure of 1.5 ton/cm², to provide tablets each weighing 570 mg.

The hardness and oral disintegration time of each tablet thus obtained were 3.2 kg and 24 seconds, respectively.

20

Example 8

(1) Production of granules having a core

A centrifugal fluidized coating granulator [manufactured by Powrex Corp. (Japan), MP-10 (Type 2)] was charged with 900 g of Nonpareil 105T (trade name) (particle diameter of 100 to 200 μm). With the inlet air temperature and the temperature of the loading being controlled at 71 to 78 °C and about 31 °C respectively, the Nonpareil was coated by spraying a bulk liquid of the following composition prepared in advance in accordance with the tangential spray method at a spray rate of 21 g /min. The spraying operation was stopped when the specified amount 5550 g of the bulk liquid had been sprayed, and then drying was carried out in the granulator for 21 minutes. The resulting granules were sieved through a #42 circular sieve (350 μm) and a #100 circular sieve (150 μm) to

35

provide 1723 g of granules having a core.

Bulk liquid:

Lansoprazole	1080 g
Magnesium carbonate	360 g
Low-substituted hydroxypropyl cellulose LH-32 (hydroxypropoxyl group contents: 8.8 weight %)	180 g
Hydroxypropyl cellulose (Type SSL)	360 g
Purified water	4680 g

- 5 (2) Production of film-undercoated granules having a core
A centrifugal fluidized coating granulator [manufactured
by Powrex Corp. (Japan), MP-10 (Type 2)] was charged with 2074
g of the above granules having a core. With the inlet air
temperature and the temperature of the loading being
10 controlled at 77 °C and about 41 °C, respectively, an
undercoating liquid of the following composition prepared in
advance was sprayed in accordance with the tangential spray
method at a spray rate of 21 g /min. The spraying operation
was stopped when the specified amount 2787 g of the undercoating
15 liquid had been sprayed, and then drying was carried out in
the granulator for 13 minutes. The resulting granules were
sieved through a #42 circular sieve (350 µm) and a #100 circular
sieve (150 µm) to provide 1958 g of film-undercoated granules
having a core.

20

Undercoating liquid:

Hydroxypropylmethylcellulose (Type 2910, viscosity: 3 centistokes)	252 g
Titanium oxide (TiO ₂)	108 g
Sterilized Talc (trade name) [produced by Matsumura Sangyo Co. Ltd. (Japan)]	108 g
Low-substituted hydroxypropyl cellulose LH-32 (hydroxypropoxyl group contents: 8.8 weight %)	180 g
Mannitol	252 g

Purified water

3600 g

(3) Production of enteric coated granules having a core
A centrifugal fluidized coating granulator [manufactured
by Powrex Corp. (Japan), MP-10 (Type 2)] was charged with 1100
g of the above film-undercoated granules having a core. With
the inlet air temperature and the temperature of the loading
being controlled at 80 °C and about 41 °C, respectively, an
enteric film coating liquid (A) of the following composition
prepared in advance was sprayed in accordance with the
tangential spray method at a spray rate of 22 g /min. The
specified amount 1365 g of the enteric film coating liquid had
been sprayed.

Enteric film coating liquid (A):

Eudragit L30D-55	1017.3 g
Eudragit NE30D	113.3 g
Polyethylene glycol 6000	34.0 g
Glyceryl monostearate	20.0 g
Polysorbate 80	6.0 g
Ferric oxide	0.2 g
Ferric oxide (yellow)	0.2 g
Citric acid anhydrous	0.4 g
Purified water	1410.8 g

15

Following this, with the inlet air temperature and the
temperature of the loading being controlled at 76 °C and about
41 °C, respectively, an enteric film coating liquid (B) of the
following composition prepared in advance was sprayed in
accordance with the tangential spray method at a spray rate
of 22 g /min. The specified amount 5040 g of the enteric film
coating liquid had been sprayed.

25

Enteric film coating liquid (B):

Eudragit L30D-55	3360 g
Eudragit NE30D	373.2 g
Triethyl citrate	224.4 g
Glyceryl monostearate	72.0 g
Polysorbate 80	21.6 g
Ferric oxide	0.72 g
Ferric oxide (yellow)	0.72 g
Citric acid anhydrous	0.6 g
Purified water	1706.8 g

Following this, with the inlet air temperature and the temperature of the loading being controlled at 80 °C and about 42 °C, respectively, an enteric film coating liquid (A) of the above mentioned composition prepared in advance was sprayed in accordance with the tangential spray method at a spray rate of 21 g /min. The specified amount 682.5 g of the enteric film coating liquid had been sprayed.

(4) Production of enteric coated and mannitol coated granules having a core

Following (3), with the inlet air temperature and the temperature of the loading being controlled at 80 °C and about 36 °C, respectively, an film coating liquid of the following composition prepared in advance was sprayed in accordance with the tangential spray method at a spray rate of 22 g /min. using a centrifugal fluidized coating granulator [manufactured by Powrex Corp. (Japan), MP-10 (Type 2)]. The spraying operation was stopped when the specified amount 735 g of the film coating liquid had been sprayed, and then drying was carried out in the granulator for 10 minutes. The resulting granules were sieved through a #35 circular sieve (420 µm) and a #60 circular sieve (250 µm) to provide 2319.5 g of enteric coated and mannitol coated granules having a core.

The average particle diameter of the obtained granules was 392.7 µm.

Film coating liquid:

Mannitol	100 g
Purified water	600 g

(5) Production of mixed powders

5 To 270 g of the above enteric coated and mannitol coated granules having a core were added 204.0 g of mannitol, 30 g of low-substituted hydroxypropyl cellulose LH-33 (hydroxypropoxyl group contents: 5.8 weight %), 30 g of crystalline cellulose [CEOLUS KG-801 (trade name),
10 manufactured by Asahi Chemical Co., Ltd. (Japan)], 15 g of crospovidone, 3 g of citric acid anhydrous, 9 g of aspartame, 6 g of magnesium stearate and 3 g of flavor [STRAWBERRY DURAROME (trade name), manufactured by Nihon Filmenich Co., Ltd. (Japan)], which was admixed in a bag to give mixed powders.

15

(6) Production of orally disintegrable tablets

570 g of the above mixed powders were tabletted using Autograph (trade name; compressing force measurement apparatus) with a punch having a beveled edge, 12 mm in
20 diameter, at a tableting pressure of 1.5 ton/cm², to provide tablets each weighing 570 mg.

The hardness and oral disintegration time of each tablet thus obtained were 3.7 kg and 35 seconds, respectively.

The acid-resistance of the obtained tablet was 3.4 %.

25

Example 9

(1) Production of granules having a core

A centrifugal fluidized coating granulator [manufactured by Powrex Corp. (Japan), MP-10 (Type 2)] was charged with 300
30 g of Nonpareil 105 (70-140) (particle diameter of 100 to 200 μ m). With the inlet air temperature and the temperature of the loading being controlled at 85 °C and about 28 °C respectively, the Nonpareil was coated by spraying a bulk liquid of the

following composition prepared in advance in accordance with the tangential spray method at a spray rate of 20 g /min. The spraying operation was stopped when the specified amount of the bulk liquid had been sprayed, and then drying was carried out in the granulator for 7 minutes. The resulting granules were sieved through a #48 circular sieve (300 μ m) and a #100 circular sieve (150 μ m) to provide 757 g of granules having a core.

10 Bulk liquid:

Lansoprazole	300 g
Magnesium carbonate	100 g
L-HPC	50 g
HPC (Type SSL)	100 g
Water	1650 g

(2) Production of film-undercoated granules having a core

A centrifugal fluidized coating granulator [manufactured by Powrex Corp. (Japan), MP-10 (Type 2)] was charged with 680 g of the above granules having a core. With the inlet air temperature and the temperature of the loading being controlled at 70 °C and about 36 °C, respectively, an undercoating liquid of the following composition prepared in advance was sprayed in accordance with the tangential spray method at a spray rate of 10 g /min. to provide 672 g of film-undercoated granules having a core.

Undercoating liquid:

HPMC	32 g
(Type 2910, viscosity: 3 centistokes)	
Talc	8 g
Water	760 g

25 (3) Production of enteric coated granules having a core

A centrifugal fluidized coating granulator [manufactured

by Powrex Corp. (Japan), MP-10 (Type 2)] was charged with 450 g of the above film-undercoated granules having a core. With the inlet air temperature and the temperature of the loading being controlled at 65 °C and about 36 °C, respectively, an enteric film coating liquid of the following composition prepared in advance was sprayed in accordance with the tangential spray method at a spray rate of 17 g /min. The coated powders were dried in vacuum at 40 °C for 16 hours, and sieved through a #42 circular sieve (355 µm) and a #80 circular sieve (177 µm) to provide 950 g of enteric coated granules having a core.

The average particle diameter of the obtained granules was 285.4 µm.

15 Enteric film coating liquid:

Eudragit L30D-55	1078.3 g
Eudragit NE30D	138.5 g
Triethyl citrate	46.0 g
Glyceryl monostearate	16.5 g
Talc	16.0 g
Polysorbate 80	9.0 g
Iron oxide	0.5 g
Water	2038.5 g

Sieve	weight ratio
#18 (850 µm) on	0 %
#30 (500 µm) on	0 %
#200 (75 µm) on	100 %
#200 (75 µm) pass	0 %

(4) Production of granulated powders

A fluidized bed granulator [manufactured by Powrex Corp. (Japan), LAB-1] was charged with 1321.2 g of erythritol [manufactured by Nikken Chemical Co., Ltd. (Japan)], 360.0 g

of low-substituted hydroxypropyl cellulose LH-32
[hydroxypropoxyl group contents of 8.8 %, manufactured by
Shin-Etsu Chemical Co., Ltd. (Japan)], 18.0 g of citric acid
anhydrous, and 1.8 g of aspartame, and granulation was carried
5 out while spraying a solution which was prepared by dissolving
3.6 g of polyethylene glycol (PEG-6000) in 896.4 ml of purified
water. The granules were dried to provide granulated powders.
To the granulated powders were added 90.0 g of crospovidone
and 5.4 g of magnesium stearate, which was admixed in a bag
10 to give mixed powders.

(5) Production of orally disintegrable tablets

200.0 g of the above enteric coated granules having a core
and 300.0 g of the above mixed powders were tabletted using
15 Autograph (trade name; compressing force measurement
apparatus) with a punch having a beveled edge, 11 mm in
diameter, at a tableting pressure of 1.0 ton/cm², to provide
tablets each weighing 500 mg.

The hardness, the oral disintegration time and remaining
20 ratio after acid-resistance test of each tablet thus obtained
were 4.2 kg, 27 seconds and 96.3 %, respectively.

INDUSTRIAL APPLICABILITY

The orally disintegrable tablet of the present invention
25 has superior disintegrability or dissolution so that it can
be used for treatment or prevention of various diseases, as
an orally disintegrable tablet capable of being administered
to the aged or children and easily administered without water.

Also, because the orally disintegrable tablet of the present
30 invention contains fine granules having the average particle
diameter and an enteric coating layer such that it will not
impart roughness in mouth, it can be administered easily
without discomfort at the administration and has superior
acid-resistance.

35 Further, because the orally disintegrable tablet of the

present invention has a suitable strength such that it will not be substantially damaged through production processes or circulation processes, it is superior in stability for long-term storage and easy of use at the administration.

5 Further, because the fine granule of the present invention is characterized in that it stably retains the acid-labile physiologically active substance, contains the physiologically active substance in high content, be small and has superior stability, it can be used for producing various
10 compact pharmaceutical preparations such as tablets, capsules, suspensions and so forth. Such preparations are easy of use at the administration. In addition, the fine granule of the present invention has superior acid-resistance
15 after compression.

CLAIMS

1. An orally disintegrable tablet which comprises (i) fine granules having an average particle diameter of 400 μm or less, which fine granules comprise a composition coated by an enteric coating layer, said composition having 10 weight % or more of an acid-labile physiologically active substance and (ii) an additive.
2. An orally disintegrable tablet of claim 1, wherein the average particle diameter of the fine granules is 300 to 400 μm .
3. An orally disintegrable tablet of claim 1, wherein the fine granules further comprise a basic inorganic salt.
4. An orally disintegrable tablet of claim 1, wherein the additive comprises a water-soluble sugar alcohol.
5. An orally disintegrable tablet of claim 1, wherein the composition coated by an enteric coating layer is further coated by a coating layer which comprises a water-soluble sugar alcohol.
6. An orally disintegrable tablet of claim 4, wherein the additive comprises (i) crystalline cellulose and/or (ii) low-substituted hydroxypropyl cellulose.
7. An orally disintegrable tablet of claim 1, wherein the particle diameter of the fine granules is practically 425 μm or less.
8. An orally disintegrable tablet of claim 1, wherein the particle diameter of the fine granules is practically 400 μm or less.
9. An orally disintegrable tablet of claim 1, wherein the acid-labile physiologically active substance is a benzimidazole compound or a salt thereof.
10. An orally disintegrable tablet of claim 9, wherein the benzimidazole compound is lansoprazole.
11. An orally disintegrable tablet of claim 3, wherein the basic inorganic salt is a salt of magnesium and/or a salt of calcium.

12. An orally disintegrable tablet of claim 1, wherein the composition comprises a core being coated by a benzimidazole compound and a basic inorganic salt, said core comprising crystalline cellulose and lactose.

5 13. An orally disintegrable tablet of claim 12, wherein the core comprises 50 weight % or more of lactose.

14. An orally disintegrable tablet of claim 12, wherein the core comprises 40 to 50 weight % of crystalline cellulose and 50 to 60 weight % of lactose.

10 15. An orally disintegrable tablet of claim 1, wherein the composition comprises 20 weight % or more of an acid-labile physiologically active substance.

16. An orally disintegrable tablet of claim 1, wherein the composition comprises 20 to 50 weight % of an acid-labile
15 physiologically active substance.

17. An orally disintegrable tablet of claim 1, wherein the fine granules are produced by fluidized-bed granulation method.

18. An orally disintegrable tablet of claim 1, wherein
20 the enteric coating layer comprises an aqueous enteric polymer agent.

19. An orally disintegrable tablet of claim 18, wherein the aqueous enteric polymer agent is a methacrylate copolymer.

20. An orally disintegrable tablet of claim 18, wherein
25 the enteric coating layer further comprises a sustained-release agent.

21. An orally disintegrable tablet of claim 20, wherein the sustained-release agent is a methacrylate copolymer.

22. An orally disintegrable tablet of claim 20, wherein
30 the sustained-release agent is in an amount of 5 to 15 weight % relative to 100 weight % of the aqueous enteric polymer agent.

23. An orally disintegrable tablet of claim 4, wherein the water-soluble sugar alcohol is erythritol.

24. An orally disintegrable tablet of claim 4, wherein
35 the water-soluble sugar alcohol is mannitol.

25. An orally disintegrable tablet of claim 5, wherein the water-soluble sugar alcohol is in an amount of 5 to 97 weight % relative to 100 weight % of the orally disintegrable tablet apart from the fine granules.

5 26. An orally disintegrable tablet of claim 4, wherein the crystalline cellulose is in an amount of 3 to 50 weight % relative to 100 weight % of the tablet apart from the fine granule.

10 27. An orally disintegrable tablet of claim 6, wherein the content of hydroxypropoxyl group in the low-substituted hydroxypropyl cellulose is 7.0 to 9.9 weight %.

28. An orally disintegrable tablet of claim 6, wherein the content of hydroxypropoxyl group in the low-substituted hydroxypropyl cellulose is 5.0 to 7.0 weight %.

15 29. An orally disintegrable tablet of claim 1, which further comprises crospovidone.

30. An orally disintegrable tablet of claim 1, wherein the oral disintegration time is one minute or less.

20 31. An orally disintegrable tablet of claim 1, which comprises no lubricant inside the tablet.

25 32. Fine granules having an average particle diameter of 400 μm or less, which comprise a composition coated by an enteric coating layer, said composition having (i) 25 weight % or more of an acid-labile physiologically active substance and (ii) a basic inorganic salt.

33. Fine granules of claim 32, wherein the average particle diameter of the fine granules is 300 to 400 μm .

34. Fine granules of claim 32, wherein the particle diameter of the fine granules is practically 425 μm or less.

30 35. Fine granules of claim 32, wherein the particle diameter of the fine granules is practically 400 μm or less.

36. Fine granules of claim 32, wherein the acid-labile physiologically active substance is a benzimidazole compound or a salt thereof.

37. Fine granules of claim 36, wherein the benzimidazole compound is lansoprazole.

38. Fine granules of claim 32, wherein the basic inorganic salt is a salt of magnesium and/or a salt of calcium.

5 39. Fine granules of claim 32, wherein the composition comprises a core being coated by a benzimidazole compound and a basic inorganic salt, said core comprising crystalline cellulose and lactose.

10 40. Fine granules of claim 39, wherein the core comprises 50 weight % or more of lactose.

41. Fine granules of claim 32, wherein the composition comprises 25 to 40 weight % of an acid-labile physiologically active substance.

15 42. Fine granules of claim 32, which are produced by fluidized-bed granulation method.

43. Fine granules of claim 32, wherein the enteric coating layer comprises an aqueous enteric polymer agent.

44. Fine granules of claim 43, wherein the aqueous enteric polymer agent is a methacrylate copolymer.

20 45. Fine granules of claim 43, wherein the enteric coating layer further comprise a sustained-release agent.

46. Fine granules of claim 45, wherein the sustained-release agent is a methacrylate copolymer.

25 47. Fine granules of claim 45, wherein the sustained-release agent is in an amount of 5 to 15 weight % relative to 100 weight % of the aqueous enteric polymer agent.

48. Fine granules of claim 32, wherein the enteric coating layer is in an amount of 50 to 70 weight % relative to 100 weight % of the fine granules.

30 49. A tablet, granule, fine granule, capsule, effervescent or suspension preparation which comprises the fine granules of claim 32.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
25 November 1999 (25.11.1999)

PCT

(10) International Publication Number
WO 99/59544 A3

- (51) International Patent Classification^a: **A61K 9/50**,
9/20, 31/44 **TABATA, Tetsuro** [JP/JP]; 9-A1-413, Yamadanishi
2-chome, Suita-shi, Osaka 565-0824 (JP).
- (21) International Application Number: **PCT/JP99/02548** (74) Agents: **ASAHINA, Tadao** et al.: Osaka Plant of Takeda
Chemical Industries, Ltd., 17-85, Jusohonmachi 2-chome,
Yodogawa-ku, Osaka-shi, Osaka 532-0024 (JP).
- (22) International Filing Date: 17 May 1999 (17.05.1999)
- (25) Filing Language: English (81) Designated States (*national*): AE, AL, AM, AU, AZ, BA,
BB, BG, BR, BY, CA, CN, CU, CZ, EE, GD, GE, HR, HU,
ID, IL, IN, IS, JP, KG, KR, KZ, LC, LK, LR, LT, LV, MD,
MG, MK, MN, MX, NO, NZ, PL, RO, RU, SG, SI, SK, SL,
TJ, TM, TR, TT, UA, US, UZ, VN, YU, ZA.
- (26) Publication Language: English
- (30) Priority Data:
10/135472 18 May 1998 (18.05.1998) JP (84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM,
10/219266 3 August 1998 (03.08.1998) JP AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT,
10/222151 5 August 1998 (05.08.1998) JP BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC,
11/5144 12 January 1999 (12.01.1999) JP NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
11/15851 25 January 1999 (25.01.1999) JP GN, GW, ML, MR, NE, SN, TD, TG).
- (71) Applicant (*for all designated States except US*): **TAKEDA**
CHEMICAL INDUSTRIES, LTD. [JP/JP]; 1-1,
Doshomachi 4-chome, Chuo-ku, Osaka-shi, Osaka
541-0045 (JP). **Published:**
— *With international search report.*
- (72) Inventors; and
- (75) Inventors/Applicants (*for US only*): **SHIMIZU, Toshi-**
hiro [JP/JP]; 5-1-608, Kitano 6-chome, Itami-shi, Hyogo
664-0007 (JP). **MORIMOTO, Shuji** [JP/JP]; 1-25, Mat-
sugaoka, Senriyama, Suita-shi, Osaka 565-0843 (JP). (88) Date of publication of the international search report:
3 May 2001
- For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

(54) Title: ORALLY DISINTEGRABLE TABLETS

(57) Abstract: An orally disintegrable tablet, of the present invention, which comprises (i) fine granules having an average particle diameter of 400 μ m or less, which fine granules comprise a composition coated by an enteric coating layer, said composition having 10 weight % or more of an acid-labile physiologically active substance and (ii) an additive, has superior disintegrability or dissolution in the oral cavity so that it can be used for treatment or prevention of various diseases, as an orally disintegrable tablet capable of being administered to the aged or children and easily administered without water. Also, because the tablet of the present invention contains fine granules having the average particle diameter such that it will not impart roughness in mouth, it can be administered easily without discomfort at the administration.

WO 99/59544 A3

INTERNATIONAL SEARCH REPORT

International Application No

PLT/JP 99/02548

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 A61K9/50 A61K9/20 A61K31/44

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A61K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 761 212 A (TAKEDA CHEMICAL INDUSTRIES LTD) 12 March 1997 (1997-03-12) page 7 -page 8; example 1 ---	1-3, 7-20, 30-45, 49
X	WO 97 25066 A (ASTRA AB ;DEPUI HELENE (SE); HALLGREN AGNETA (SE)) 17 July 1997 (1997-07-17) page 23 -page 25; example 1 --- -/--	1-3, 6-9, 11, 15-20, 26, 29-36, 38, 41-45, 48, 49

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

5 November 1999

Date of mailing of the international search report

11/11/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Boulois, D

INTERNATIONAL SEARCH REPORT

International Application No
PCT/JP 99/02548

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 96 24375 A (ASTRA AB ;DEPUI HELENE (SE); ROSINSKI ADAM (SE)) 15 August 1996 (1996-08-15) page 28 -page 30; example 5	1-3, 6-11, 15-20, 26, 29-38, 41-45, 48,49
X	WO 96 01624 A (ASTRA AB ;BERGSTRAND PONTUS JOHN ARVID (SE); LOEVGREN KURT INGMAR) 25 January 1996 (1996-01-25) page 19 -page 20; example 1 page 23 -page 24; example 4	1-3, 6-11, 15-20, 26, 29-38, 41-45, 48,49
A	WO 87 02240 A (HAESSLE AB) 23 April 1987 (1987-04-23) page 6 -page 7; example 1	1-49
A	EP 0 446 961 A (TAKEDA CHEMICAL INDUSTRIES LTD) 18 September 1991 (1991-09-18) page 11 -page 12; example 1	1-49
A	EP 0 799 616 A (TAKEDA CHEMICAL INDUSTRIES LTD) 8 October 1997 (1997-10-08) page 12 -page 13; examples 7,21	1-49

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/JP 99/02548

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0761212 A	12-03-1997	CA 2184964 A JP 9132522 A US 5824339 A	09-03-1997 20-05-1997 20-10-1998
WO 9725066 A	17-07-1997	AU 1324197 A BR 9607350 A CA 2213996 A CN 1183047 A CZ 9702747 A EP 0813424 A JP 11501950 T NO 974071 A NZ 325977 A PL 322175 A SK 116997 A	01-08-1997 30-12-1997 17-07-1997 27-05-1998 18-03-1998 29-12-1997 16-02-1999 17-10-1997 25-02-1999 19-01-1998 06-05-1998
WO 9624375 A	15-08-1996	AU 689372 B AU 4682296 A BR 9605111 A CA 2186039 A CN 1148344 A CZ 9602931 A EP 0754061 A FI 963984 A HR 960032 A HU 9603064 A JP 9511767 T NO 964212 A NZ 301408 A PL 316684 A SK 126096 A TR 970235 T ZA 9600365 A	26-03-1998 27-08-1996 07-10-1997 15-08-1996 23-04-1997 12-11-1997 22-01-1997 04-10-1996 31-10-1997 28-08-1997 25-11-1997 04-10-1996 28-07-1998 03-02-1997 07-05-1997 21-03-1997 06-08-1996
WO 9601624 A	25-01-1996	AU 695971 B AU 2993895 A BR 9506028 A BR 9506029 A CA 2170644 A CA 2170995 A CN 1134667 A CN 1134668 A CZ 9600730 A EP 0723437 A EP 0724434 A FI 961058 A FI 961059 A HU 75934 A JP 9502740 T JP 9502741 T NO 960948 A NO 960949 A NZ 289949 A PL 313388 A PL 313389 A WO 9601625 A SK 30096 A TR 960037 A	27-08-1998 09-02-1996 14-10-1997 14-10-1997 25-01-1996 26-01-1996 30-10-1996 30-10-1996 17-07-1996 31-07-1996 07-08-1996 07-03-1996 07-03-1996 28-05-1997 18-03-1997 18-03-1997 07-03-1996 07-03-1996 27-07-1997 24-06-1996 24-06-1996 25-01-1996 10-09-1997 21-06-1996

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/JP 99/02548

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9601624 A		TR 960038 A US 5753265 A ZA 9505546 A ZA 9505547 A	21-06-1996 19-05-1998 08-01-1996 08-01-1996
WO 8702240 A	23-04-1987	SE 450087 B AT 62409 T AU 593038 B AU 6529686 A CA 1293449 A CN 1025283 B CS 8607294 A CY 1764 A DD 266734 A DK 287687 A EP 0277127 A ES 2003139 A FI 881657 A,B, GR 862526 A HK 11494 A IE 58967 B JP 2560019 B JP 63501080 T KR 9400098 B LT 2310 R LV 5394 A LV 5750 A LV 5827 A NO 175514 B NZ 217697 A PH 24739 A PT 83508 A,B SE 8504720 A SG 8094 G SU 1706373 A US 5246714 A US 4927640 A	09-06-1987 15-04-1991 01-02-1990 05-05-1987 24-12-1991 06-07-1994 14-08-1989 15-07-1994 12-04-1989 04-06-1987 10-08-1988 16-10-1988 08-04-1988 09-02-1987 18-02-1994 01-12-1993 04-12-1996 21-04-1988 05-01-1994 15-12-1993 10-03-1994 20-12-1996 20-01-1998 18-07-1994 26-04-1989 01-10-1990 01-11-1986 12-04-1987 15-04-1994 15-01-1992 21-09-1993 22-05-1990
EP 0446961 A	18-09-1991	EP 0423748 A BG 61202 B CA 1327010 A CA 1338377 A CA 1338399 A DE 3750431 D DE 3750431 T DE 3751845 D DE 3751845 T DE 3780045 A EP 0237200 A HK 188195 A HK 1002021 A SG 50619 A US 5045321 A US 5433959 A US 5639478 A US 5093132 A US 5246712 A US 5879708 A	24-04-1991 28-02-1997 15-02-1994 11-06-1996 18-06-1996 29-09-1994 22-12-1994 25-07-1996 28-11-1996 06-08-1992 16-09-1987 22-12-1995 24-07-1998 20-07-1998 03-09-1991 18-07-1995 17-06-1997 03-03-1992 21-09-1993 09-03-1999

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/JP 99/02548

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0446961 A		JP 1893359 C	26-12-1994
		JP 3038247 B	10-06-1991
		JP 62277322 A	02-12-1987
EP 0799616 A	08-10-1997	CA 2201413 A	01-10-1997
		JP 10081621 A	31-03-1998
		US 5846562 A	08-12-1998